Submittal Sheet

Submittal Sheet #0309412

Bugle Head Streaker® Screws (212)

Product:	ltem#	Description	Unit Pack
	C368	6 x 1-1/4-in, Bugle Head, Fine Thread, Streaker®, Phosphate, Collated	1,000
	1268YZ	10 x 3-1/2-in, Bugle Head, Fine Thread, STREAKER®, Yellow Zinc, Bulk	1,000
	C8100UC	8 x 1-in, Undercut Head, Fine Thread, Streaker®, Yellow Zinc, Collated	1,000
	C368RG	6 x 1-1/4-in, Bugle Head, Fine Thread, Streaker®, GrabberGard®, Collated	1,000
	268RG	6 x 1-1/8-in, Bugle Head, Fine Thread, Streaker® GrabberGard®, Bulk	10,000
	168Z	6 x 1-in, Bugle Head, Fine Thread, Clear Zinc, Bulk	10,000
	168	6 x 1-in, Bugle Head, Fine Thread, Phosphate, Bulk	10,000
	C368RG8	8 x 1-1/4-in, Bugle Head, Fine Thread, Streaker®, GrabberGard®, Collated	1,000
	1168Z	8 x 3-in, Bugle Head, Fine Thread, Clear Zinc, Bulk	2,000
	968Z	8 x 2-1/2-in, Bugle Head, Fine Thread, Clear Zinc, Bulk	2,500
	768Z	6 x 2-in, Bugle Head, Fine Thread, Clear Zinc, Bulk	3,500
	468Z	6 x 1-5/8-in, Bugle Head, Fine Thread, Clear Zinc, Bulk	5,000
	468RG	6 x 1-5/8-in, Bugle Head, Fine Thread, Streaker®, GrabberGard®, Bulk	5,000
	368Z	6 x 1-1/4-in, Bugle Head, Fine Thread, Streaker®, Bulk	8,000
	368RG	6 x 1-1/4-in, Bugle Head, Fine Thread, Streaker®, GrabberGard®, Bulk	8,000
	268Z	6 x 1-1/8-in, Bugle Head, Fine Thread, Clear Zinc, Bulk	10,000
	1268	10 x 3-1/2-in, Bugle Head, Fine Thread, Phosphate, Bulk	1,000
	1368	10 x 4-in, Bugle Head, Fine Thread, Phosphate, Bulk	1,000
	1468	10 x 4-1/2-in, Bugle Head, Fine Thread, Phosphate, Bulk	1,000
	1568	10 x 5-in, Bugle Head, Fine Thread, Phosphate, Bulk	1,000
	1768	10 x 6-in, Bugle Head, Fine Thread, Phosphate, Bulk	1,000
	368	6 x 1-1/4-in, Bugle Head, Fine Thread, Phosphate, Bulk	8,000
	268	6 x 1-1/8-in, Bugle Head, Fine Thread, Phosphate, Bulk	10,000
	468	6 x 1-5/8-in, Bugle Head, Fine Thread, Phosphate, Bulk	5,000
	768	6 x 2-in, Bugle Head, Fine Thread, Phosphate, Bulk	3,500
	868	7 x 2-1/4-in, Bugle Head, Fine Thread, Phosphate, Bulk	3,000
	968	8 x 2-1/2-in, Bugle Head, Fine Thread, Streaker ${ m extsf{R}}$, Phosphate, Bulk	2,500
	1168	8 x 3-in, Bugle Head, Fine Thread, Phosphate, Bulk	2,000
	1368YZ	10 x 4-in, Bugle Head, Fine Thread, STREAKER®, Yellow Zinc, Bulk	1,000
	1568YZ	10 x 5-in, Bugle Head, Fine Thread, STREAKER®, Yellow Zinc, Bulk	1,000
	1768YZ	10 x 6-in, Bugle Head, Fine Thread, STREAKER®, Yellow Zinc, Bulk	1,000
	C468	6 x 1-5/8-in, Bugle Head, Fine Thread, Streaker ${ m I\!R}$, Phosphate, Collated	1,000
	C768	7 x 2-in, Bugle Head, Fine Thread, Streaker ${ m (B)}$, Phosphate, Collated	1,000

Screw Series	Designation	Head Type	Nominal Diameter	Nominal Head Diameter	Nominal Gauge- TPI	Nominal Length	Point (No#)	Thread Length	Drilling Capacity Min#	Drilling Capacity Max#	Coating
Streaker	Light Gauge Steel	Bugle Head	0.138	0.321	#6-15	1	Streaker	0.875	25 ga.	20 ga.	P, Z
Streaker	Light Gauge Steel	Bugle Head	0.138	0.321	#6-15	1.25	Streaker	1.125	25 ga.	20 ga.	P, Z, RG
Streaker	Light Gauge Steel	Bugle Head	0.138	0.321	#6-15	1.125	Streaker	0.92	25 ga.	20 ga.	P, Z, RG
Streaker	Light Gauge Steel	Bugle Head	0.138	0.321	#6-15	1.625	Streaker	1.5	25 ga.	20 ga.	P, Z, RG
Streaker	Light Gauge Steel	Bugle Head	0.138	0.321	#6-15	2	Streaker	1.875	25 ga.	20 ga.	P, Z
Streaker	Light Gauge Steel	Bugle Head	0.151	0.321	#7-19	2.25	Streaker	2	25 ga.	20 ga.	P, Z
Streaker	Light Gauge Steel	Bugle Head	0.164	0.321	#8-15	1.25	Streaker	1.125	25 ga.	20 ga.	RG
Streaker	Light Gauge Steel	Bugle Head	0.164	0.321	#8-15	2.5	Streaker	2.02	25 ga.	20 ga.	P, Z
Streaker	Light Gauge Steel	Bugle Head	0.164	0.321	#8-15	3	Streaker	2.02	25 ga.	20 ga.	P, Z
Streaker	Light Gauge Steel	Bugle Head	0.19	0.343	#10-12	3.5	Streaker	2.02	25 ga.	20 ga.	P, Z
Streaker	Light Gauge Steel	Bugle Head	0.19	0.343	#10-12	4	Streaker	2.02	25 ga.	20 ga.	P
Streaker	Light Gauge Steel	Bugle Head	0.19	0.343	#10-12	4.5	Streaker	2.02	25 ga.	20 ga.	P
Streaker	Light Gauge Steel	Bugle Head	0.19	0.343	#10-12	5	Streaker	2.02	25 ga.	20 ga.	P
Streaker	Light Gauge Steel	Bugle Head	0.19	0.343	#10-12	6	Streaker	2.02	25 ga.	20 ga.	Р
Applicatior	•	1/2" and 5 1/2" and n	/8″ single-l nultiple-laye od cabinets	ayer gypsu er gypsum l s through si	m board to s board to stee	steel studs el studs an	eel or wood. and track d track ard to steel s		-		
Descriptior	p • •	oint. Availal A fine-three Ideal for us Super shar #2 Phillips	ble in Grab ad screw fo se with 20 c p, 23° STRE recess drive	berGard® r general ir Ind 25 gau AKER® Poir e	Exterior finis nterior applic ge steel 12 - nt, designed	h and clea cations - 15 thread to penetro	hate finish w r zinc silver f ds per inch ate steel quic soft wood or a	inish. kly and ec	isily		
Directions:	 Tections: Use a standard screwgun with a depth-sensitive nose piece. Suggested screwgun specifications for optimal performance – 4 amps minimum and RPM range of 0 – 4000. The bugle head is fully seated when the head is flush with the work surface. Overdriving may result in failure of the STREAKER® or stripout of the work surface. The STREAKER® must penetrate beyond the metal a minimum of three thread pitches. 										
Certificatio	All GRABBER® screw products are manufactured in facilities that are ISO 9002 and ISO 14001 certified and approved. The fasteners comply with ASTM C1002, as referenced in ICCES report ER-5280 are approved for use ir structures governed by the International Building Code 2006, 2009, 2012, International Residential Building Code 2006, 2009, 2009, and 2012.										



Bugle Head Fine Thread Streaker®





Submittal	Sheet	#0309	412
-----------	-------	-------	-----

SUBMITTAL APPROVALS:

.....

JOB NAME

CONTRACTOR

DATE

.....

TRADEMARKS:

The following trademark used herein is owned by Grabber Construction Products, Inc.: GRABBER.

NOTICE:

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our Liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days of the date it was or reasonably should have been discovered.

Bugle Head Streaker® Screws (212)



PRODUCT SPECIFICATIONS	
Fastener Classification	Interior Wood, Light Gauge Metal (20-25)
Fastener Head	Bugle, Undercut
Fastener Drive	#2 Phillips
Fastener Gauge	#6, #7, #8, #10
Fastener Point	Streaker
Fastener Package Type	Packaged Screws, Collated Screws (for automated feed systems)
Fastener Package Weight	Mini Pack, 1lb Box, 5 Pound, 5lb Box, Bulk Box
Fastener TPI	12, 14, 15
Fastener Coating	Black/Gray Phosphate, Yellow Zinc, Clear Zinc, GrabberGard
Fastener Color	Gray, Yellow

STANDARD CORROSION TEST RESULTS					
Finish	Test	Standard/Protocol	Results		
Gray Phosphate	Salt Spray Results	ASTM B117	24 hours, no red rust		
Yellow Zinc	Salt Spray Results	ASTM B117	48 hours, no red rust		
Clear Zinc	Salt Spray Results	ASTM B117	24 hours, no red rust		
Dracrotized	Salt Spray Results	ASTM B117	500 hours, no red rust		
GrabberGard	Salt Spray Results	ASTM B117	1,000 hours, no red rust		
GrabberGard	Kesternich Results	DIN 50018, 2.0L	15 cycles, no red rust		
304 Stainless Steel	Salt Spray Results	ASTM B117	1000 hours, no red rust		
316 Stainless Steel	Salt Spray Results	ASTM B117	1500 hours, no red rust		

Grabber's approved mill keeps tight control over all production standards and processes. Grabber's mill is ISO 9001, ISO 14001 and ICC-ES certified compliant ensuring Grabber fasteners meet or exceed the highest industry standards.