



350 Step A Bull

| STOCK NUMBER | LENGTH | PCS PER BOX |
|-----------------|--------|----------------|
| 7038 | 8' | 20 |
| 7030 | 10' | 20 |



| STOCK NUMBER | LENGTH | PCS PER BOX |
|-----------------|--------|----------------|
| 7048 | 8' | 15 |
| 7040 | 10' | 15 |



10'

10

7050

SUBMITTAL SHEET

Product(s): Trim-Tex Step A Bull Beads

Description: Trim-Tex Step A Bull Beads are available in 3 different sizes and have a stepped in radius to create a beautiful bullnose look with sharp crisp edges. Perfect for outside corners, decorative columns, soffits & niches.

Advantages: Creates crisp lines great for paint transitions while maintaining the bullnose look. Made from rust proof, dent resistant PVC to reduce jobsite and handling damage.

Limitations: Product is designed for interior use.

Applicable Standards: Rigid PVC products made by Trim-Tex meet ASTM specifications D3678-97, D1784-03, C1047-99 and achieve a Class A rating for flame spread and smoke developed when tested under ASTM E84-10.

Surface Characteristics: Trim-Tex products are made from PVC. PVC does not support combustion and is self extinguishing when the source of flame or heat is removed.

Installation: Set back the drywall for outside corners if required. Install Molded Corners and/or Bull Adapters if required first. Snip the bead to length and dry fit. Install with Trim-Tex 847 Spray Adhesive and $\frac{1}{2}$ " divergent staples every 6-8".

Finishing: To improve the bondability of drywall compounds, textures & plaster products to any bead, use MUD-MAX Drywall Compound Additive. Priming is not required. Always use a high quality paint.

Accessories: 2 Way & 3 Way Molded Corners, Step ABull Adapters, 847 Spray Adhesive, Mud-Max, Trim-Tex Sanding Blocks & Abrasive Products, Mud-Max Drywall Compound Additive, North Safety Products distributed by Trim-Tex.

| Job Name | |
|------------|------|
| | |
| Contractor | Date |

Approvals (Signatures or Stamps)