

**DESCRIPTION**

Patented PVC fiber composite material patch measures 36" x 2-1/2", and .013" thickness. Contoured to match corrugated steel decking of all manufacturers, Deck-Patch is the fastest way of finishing drywall to corrugated steel decking. Perforated in three foot sections and in the center, Deck-Patch works great as a template for cutting drywall to fit the corrugated decking. Deck-Patch will not fuzz-up during sanding.

**ADVANTAGES**

- 102 LF per box.
- Cuts easily with scissors or knife.
- Perforated in three foot sections and in the center for easy handling.
- Great as a template for cutting drywall to fit the corrugated decking.
- PVC fiber composite material.
- Specify decking manufacturer and item number when ordering Deck-Patch.
- Easily installs using standard drywall compounds. .

**WARRANTY**

Strait-Flex products are backed by a lifetime warranty. When applied to a sound structure, built on a permanent foundation using recommended application techniques, we warrant that these products will not edge-crack for the lifetime of the structure. Not recommended where structural movement may occur. Contact Strait-Flex International Inc for complete details.

**DIRECTIONS**

- To apply, lightly sand area to be repaired.
- Apply drywall compound 1/8"-1/4" thick directly to back of patch.
- Place patch over center of repair and wipe down flat to wall using joint knife.
- Immediately skim-coat patch and let dry.
- Apply second coat, let dry, and sand. Compound that remains on backside of Deck-Patch makes patch very rigid in the damaged area.

**STORAGE**

Store in dry place protected from moisture.

**SUBMITTAL APPROVALS**

\_\_\_\_\_  
JOB NAME

\_\_\_\_\_  
CONTRACTOR

\_\_\_\_\_  
DATE

