

# Ecophon®

Akusto™ One SQ  
 VOC Compliant

LOW  
VOC

\$\$\$\$



LEED® v4

- MR: Environmental Product Declarations (EPDs)
- MR: Sourcing Raw Materials
- MR: Material Ingredients (HPDs)
- IEQ: Daylight
- IEQ: Low-Emitting Materials
- IEQ: Prereq. Min. Acoustic Performance (Schools)
- IEQ: Acoustic Performance
- MR: PBT Source Reduction (Healthcare)
- IEQ: Interior Lighting
- EA: Prereq. Min. Energy Performance
- EA: Optimize Energy Performance
- Recycled Content  
Pre: **1%** | Post: **70%**

## TOOLS

Visit [CertainTeed.com/Ceilings](https://www.certainteed.com/Ceilings)  
 Download HPDs and EPDs  
 LEED® Information / BIM Objects  
 3-Part Specs / Data Pages

# EPD®



## FEATURES & BENEFITS

- Exclusive 3RD™ technology combines high recycled glass content with a renewable plant-based binding agent, completely replacing traditional petroleum-based binding
- Reduces echoes and improves speech clarity within a room
- Endless design possibilities with different formats and colors to create various patterns
- Quick installation with two options to fix panels to the wall
- Frameless panels with fully painted white or gray edges
- Smooth, Texona fabric surface is impact resistant and available in a variety of colors
- Vertically installed










## APPLICATIONS

- Open Plan Offices
- Classrooms
- Libraries
- Conference Rooms
- Other Commercial Buildings / Space Applications



Akusto™ One SQ Wall Panels (Thyme, Pepper, Poppyseed)

## ATTRIBUTES

	COLOR	DIMENSIONS (MM) (≈ INCHES)	SHAPE	 NRC	 HPD AVAILABLE	 EPD AVAILABLE	 MOLD RESISTANT	 LR	 WASHABLE	 FIRE CLASS (ASTM E1264)	 EMISSION COMPLIANT	 RECYCLED CONTENT
<b>AKUSTO™ ONE SQ WALL PANELS — WHITE EDGE</b>												
<b>3557 4026</b>	Sea Salt	300 x 1200 x 40 (≈ 12 x 48)	Rectangle	0.95	—	Yes	Inherent	0.81	—	Class A	Certified	71%
<b>3557 4000</b>	Sea Salt	600 x 600 x 40 (≈ 24 x 24)	Square	0.95	—	Yes	Inherent	0.81	—	Class A	Certified	71%
<b>3557 4052</b>	Sea Salt	600 x 1200 x 40 (≈ 24 x 48)	Rectangle	0.95	—	Yes	Inherent	0.81	—	Class A	Certified	71%
<b>3557 4078</b>	Sea Salt	600 (≈ D24)	Circle	0.95	—	Yes	Inherent	0.81	—	Class A	Certified	71%
<b>3557 4104</b>	Sea Salt	800 (≈ D32)	Circle	0.95	—	Yes	Inherent	0.81	—	Class A	Certified	71%
<b>3557 4130</b>	Sea Salt	1200 (≈ D48)	Circle	0.95	—	Yes	Inherent	0.81	—	Class A	Certified	71%
<b>AKUSTO™ ONE SQ WALL PANELS — GRAY EDGE</b>												
<b>3557 4039</b>	Sea Salt	300 x 1200 x 40	Rectangle	0.95	—	Yes	Inherent	0.81	—	Class A	Certified	71%
<b>3557 4013</b>	Sea Salt	600 x 600 x 40	Square	0.95	—	Yes	Inherent	0.81	—	Class A	Certified	71%
<b>3557 4065</b>	Sea Salt	600 x 1200 x 40	Rectangle	0.95	—	Yes	Inherent	0.81	—	Class A	Certified	71%
<b>3557 4091</b>	Sea Salt	600 (≈ D24)	Circle	0.95	—	Yes	Inherent	0.81	—	Class A	Certified	71%
<b>3557 4117</b>	Sea Salt	800 (≈ D32)	Circle	0.95	—	Yes	Inherent	0.81	—	Class A	Certified	71%
<b>3557 4143</b>	Sea Salt	1200 (≈ D48)	Circle	0.95	—	Yes	Inherent	0.81	—	Class A	Certified	71%

Contact your local Sales Representative or call 800-233-8990 to order Akusto One SQ in any Texona color

## PHYSICAL DATA

**MATERIAL**  
Fiberglass

**FIRE CLASS (ASTM E1264)**  
Tested according to ASTM E84 & CAN S102  
Flame Spread: 25 or less  
Smoke Developed: 50 or less

**VOC EMISSIONS**  
Independently certified compliant with California  
Department of Public Health CDPH/EHLB/Standard  
Method Version 1.1, 2010.

**MOLD/MILDEW RESISTANCE**  
Fiberglass substrate is inherently resistant to the growth  
of mold and mildew.

**MAINTENANCE**  
Wipe with a soft cloth or vacuum with brush attachment.

**WARRANTY**  
10-year Ecophon® Warranty