

## Rockfon Artic®

**0.75**  
NRC

### Features & Benefits

- Smooth white surface
- Economic solution with standard sound absorption (NRC = 0.75)
- High fire performance
- Lightweight panel, easy to carry and install
- Available in square lay-in and tegular

### Applications

- Retail
- Corridor
- Break Room
- Waiting Room



Rockfon ceiling tiles are manufactured using advanced stone wool technology. All stone wool tiles benefit from:



**High Acoustic Absorption**



**Class A Fire Rated Performance**



**Moisture and Sag Resistance**



**Smooth, Modern Aesthetics**

### Materials and Resources (MR)

- Waste Management Planning
- Interiors Life Cycle Impact Reduction
- Environmental Product Declarations
- Sourcing of Raw Materials
- Material Ingredients
- Waste Management

### Indoor Environmental Quality (EQ)

- Low-Emitting Materials ✓
- ✓ Interior Lighting ✓
- ✓ Acoustic Performance ✓

**Recycled Content:** up to 47%



## Standard Panels

### Packaging Information

Edge Designation	Item Number	Modular Size (nominal)	NRC	AC	Fire Class	Light Reflectance	Sag Resistance (relative humidity)	Low VOC	lbs/sqft	sqft/carton
	SQ 600	2' x 2' x 5/8"	0.75	-	A	0.85	up to 100%	✓	0.38	112
	SQ 601	2' x 4' x 5/8"	0.75	-	A	0.85	up to 100%	✓	0.38	112
	SQ 609	20" x 60" x 3/4"	0.75	-	A	0.85	up to 100%	✓	0.45	83.33
	SQ 610	2' x 5' x 3/4"	0.75	-	A	0.85	up to 100%	✓	0.45	100
	SLN 620	2' x 2' x 5/8"	0.75	-	A	0.85	up to 100%	✓	0.47	56
	SLN 621	2' x 4' x 5/8"	0.75	-	A	0.85	up to 100%	✓	0.47	112
	SL 660	2' x 2' x 5/8"	0.75	-	A	0.85	up to 100%	✓	0.47	56
	SL 661	2' x 4' x 5/8"	0.75	-	A	0.85	up to 100%	✓	0.47	112

15/16" Suspension Systems	9/16" Suspension Systems
200, 1200 and Fire Rated systems	4000, 4500, 4600 and Fire Rated systems
SQ - Square Lay-In    SL - Square Tegular 	SQ - Square Lay-In (2' x 2' & 2' x 4' only)    SLN - Square Tegular Narrow 
	4000 - Tempra    4000 - Tempra    4500 - Ultraline 1/4" reveal    4600 - Ultraline 1/8" reveal



## Rockfon Artic Properties

### Material

Stone wool (Mineral Wool) ceiling tiles with factory applied latex paint on glass scrim surface  
ASTM E1264 CLASSIFICATION: Type XX - Stone wool base with membrane-faced overlay, Pattern G



### Fire Performance

Surface burning characteristics:  
UL723 (ASTM E84) Flame Spread Index: 0  
Smoke Developed Index (UL Labeled): 5  
CAN/ULC S102 Flame Spread Index: 5  
Smoke Developed Index: 0



### Environment

Up to 47% recycled content.  
Recycled content based on U.S. manufacturing.



### Thermal Insulation

R Value (BTU Units): 2.2 - 2.6  
RSI Value (Watts Units): 0.39 - 0.46



### Sustainability

Many of Rockfon stone wool acoustic solutions are GREENGUARD Gold low VOC certified and meet the State of California's Department of Public Health Services Standard Practice for Specification Section 01350 (California Section 01350) for testing chemical emissions.

Selected potential applications: LEED, WELL, CHPS, Green Globes, BREEAM Int. and CALGreen.



### Warranty

30-Year Limited Product Warranty.  
See [rockfon.com](http://rockfon.com)



### Hygiene

Stone wool provides no sustenance to microorganisms



### Cleaning

- Vacuum



Greenguard Gold Certified for Office and Educational Environments

2019 | Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.  
© ROCKWOOL International A/S 2018. All rights reserved.  
® denotes a trademark that is registered in the United States of America.

112619

**Rockfon**

4849 S. Austin Ave.  
Chicago, IL 60638 USA

Tel. +1-800-323-7164

Fax. +1-800-222-3744

[rockfon.com](http://rockfon.com)