

Calla® Vector® panels with Prelude® 15/16" suspension system (Pgs. 391-392)

Calla® Vector® panels are great for projects where plenum space is limited and a sleek, monolithic visual is desired.

**KEY SELECTION ATTRIBUTES**

- Smoothest mineral fiber panel available
- 1/4" reveal resulting in a monolithic appearance
- Calla® Vector® panels are part of the Sustain™ portfolio and meet the most stringent sustainability compliance standards today
- Washable, scratch-resistant, soil-resistant
- Excellent sound absorption – NRC (0.80)
- Downward accessible for minimal plenum height
- USDA Certified Biobased Product – 59%
- Product can be recycled through the Armstrong Ceilings Recycling Program
- 30-Year Limited System Warranty against visible sag, mold, and mildew

**TYPICAL APPLICATIONS**

- Renovation – installs on existing 15/16" suspension
- Open plan offices
- Corridors
- Lobbies/reception areas
- Retail

**COLOR**



White  
(WH)




Made-to-order  
Sherwin-Williams®  
Colors Available

**DETAILS** (Other Suspension Systems compatible. Refer to listing on page 320.)



1



2

1. Calla® Vector®
2. Calla Vector with Prelude® 15/16" suspension system


**VISUAL SELECTION**

\$\$\$

Edge Profile	Susp. Dwg. Pgs. 407-411 armstrongceilings.com/catdwgs	Item No.	Dimensions (Inches)	UL Classified Acoustics		Total Acoustics <sup>1</sup>	Articulation Class	Fire Performance	Light Reflect	Anti-Mold & Mildew	Sag Resist	Certified Low VOC Emissions	Wash	Scratch	Soil	Recycled Content	Recycle Program	30-Yr Warranty
				NRC	CAC													
CALLA® Vector® 1/4" Reveal with 15/16" Vector	73	<b>2814</b>	24 x 24 x 1"	0.80	33	-	170	Class A	0.86	•	•	•	•	•	•	•	•	•
CALLA® Vector® 1/4" Reveal with 15/16" Vector	73	<b>2815</b>	24 x 48 x 1"	0.80	33	-	170	Class A	0.86	•	•	•	•	•	•	•	•	•

<sup>1</sup> Total Acoustics® ceiling panels have an ideal combination of noise reduction and sound-blocking performance in one product.  
**GOOD** (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)

**SUSPENSION SYSTEMS**



**VECTOR – FIXTURE TRIMS**

Item No.	Length	Color	Substrate	Pcs per Carton
<b>5790</b>	12"	White	Extruded PVC	48
<b>5791</b>	24"	White	Extruded PVC	48
<b>5792</b>	30"	White	Extruded PVC	48
<b>5793</b>	48"	White	Extruded PVC	48

**ACCESSORIES (must be ordered separately)**

Item No.		Pcs per Carton
<b>443</b>	Calla Vector® Border Clip	50
<b>7425</b>	24" Stabilizer Bar	100
<b>7445</b>	48" Stabilizer Bar	100
<b>7870</b>	Spring Border Clip (For installations with the panel resting on the wall molding)	1,000

**PHYSICAL DATA**

**Material**  
 Wet-formed mineral fiber with an acoustically transparent membrane.

**Surface Finish**  
 Acoustically transparent membrane with factory-applied latex paint.

**Fire Performance**  
 ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less (UL labeled).

**ASTM E1264 Classification**  
 Type IV, Form 2, Pattern E  
 Fire Class A

**Humidity/Sag Resistance**  
 HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

**Mold/Mildew Protection**  
 Ceiling panels with BioBlock® performance resist the growth of mold and mildew.

**VOC Emissions**  
 Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010. This standard is the guideline for low emissions in LEED, CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

**Acoustical Performance**  
 CAC testing conducted using Prelude® XL® suspension system.

**High Recycled Content**  
 Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

**Insulation Value**  
 R Factor – 2.9 (BTU units)  
 R Factor – 0.445 (Watts units)

**30-Year Performance Guarantee & Warranty**  
 When installed with Armstrong® Suspension System. Details at armstrongceilings.com

**Weight; Square Feet/Carton**  
 2814 – 1.0 lbs/SF; 40 SF/ctn  
 2815 – 1.0 lbs/SF; 48 SF/ctn

**Minimum Order Quantity**  
 1 carton