CGC SHEETROCK® BRAND ULTRALIGHT PANELS FIRECODE® X

GREATER PERFORMANCE WITH NONE OF THE WEIGHT.

CGC Sheetrock® Brand UltraLight Panels Firecode® X are the industry's first wallboard that's both lightweight and Type X. They now offer you one solution for fire-rated wall, floor-ceiling and roof-ceiling assemblies.

- Weigh up to 28% less than standard 15.9 mm (5/8 in.)
 Type C and 22% less than Type X panels, resulting in reduced worker fatigue and greater job site productivity
- Less weight also means reduced wear and tear on delivery and stocking equipment
- Feature superior score and snap for cleaner edge and faster installation
- Assemblies which meet the National Building Code sound performance requirement of a Sound Transmission Class (STC) of 50 and an Apparent Sound Transmission Class (ASTC) of 47 for wall partitions and floor-ceilings
- Reduce material cost and installation time by requiring 25% fewer resilient channels spaced at 406 mm (16 in.) OC on Open-Web wood trusses
- Listed in the most widely specified UL Designs for wall, floor-ceiling and roof-ceiling assemblies, including U419, L521, L528, M521, M522, M525, M532 and P522 (refer to specific UL Designs for complete details)

Experience the difference at cgcinc.com

WB2982-CAN-B/12-17

© 2017 USG Corporation and/or its affiliates. All rights reserved.
The trademarks CGC, FIRECODE, SHEETROCK, IT'S YOUR WORLD. BUILD IT., the CGC logo, the design elements and colours, and related marks are trademarks of USG Corporation or its affiliates.

REENGUARD Certified products are certified to GREENGUARD standards for low cl



