

Rockfon® Color-all™

UP TO
0.95
NRC

Features & Benefits

- 34 exclusive colors organized in 6 themes
- Smooth surface
- Excellent sound absorption (NRC = 0.85 - 0.95)
- High fire performance
- Optimal design freedom due to the variety of edges (lay-in, tegular and concealed) and colors

Applications

- Office
- Classroom
- Restaurant
- Reception
- Auditorium



Rockfon ceiling tiles are manufactured using advanced stone wool technology. All stone wool tiles benefit from:



High Acoustic Absorption



Class A Fire Rated Performance



Moisture and Sag Resistance



Smooth, Modern Aesthetics

Materials and Resources (MR)

- Waste Management Planning
- Interiors Life Cycle Impact Reduction
- Environmental Product Declarations
- Sourcing of Raw Materials
- Material Ingredients
- Waste Management

Indoor Environmental Quality (EQ)

- Low-Emitting Materials ✓
- ✓ Interior Lighting ✓
- ✓ Acoustic Performance ✓

Recycled Content: up to 29%



Standard Panels



Packaging Information

Edge Designation	Item Number	Modular Size (nominal)	NRC	AC	Fire Class	Light Reflectance	Sag Resistance (relative humidity)	Low VOC	lbs/sqft	sqft/carton	
	SQ	11100	2' x 2' x 5/8"	0.85	-	A	Color Dependant	up to 100%	✓	0.47	112
	SQ	11101	2' x 4' x 5/8"	0.85	-	A	Color Dependant	up to 100%	✓	0.47	112
	SL	11250	2' x 2' x 3/4"	0.95	-	A	Color Dependant	up to 100%	✓	0.69	40
	SL	11251	2' x 4' x 3/4"	0.95	-	A	Color Dependant	up to 100%	✓	0.69	80
	SLN	11200	2' x 2' x 3/4"	0.95	-	A	Color Dependant	up to 100%	✓	0.69	40
	SLN	11201	2' x 4' x 3/4"	0.95	-	A	Color Dependant	up to 100%	✓	0.69	80
	CDX	11600	2' x 2' x 7/8"	0.95	-	A	Color Dependant	up to 100%	✓	0.75	40
	CDX	11601	2' x 4' x 7/8"	0.95	-	A	Color Dependant	up to 100%	✓	0.75	80

15/16" Suspension Systems	9/16" Suspension Systems
200, 1200 and Fire Rated systems	4000, 4500, 4600 and Fire Rated systems
SQ - Square Lay-In SL - Square Tegular CDX - Fully Concealed 	SQ - Square Lay-In SLN - Square Tegular Narrow
	4000 - Tempra 4000 - Tempra 4500 - Ultraline 1/4" reveal 4600 - Ultraline 1/8" reveal



Rockfon Color-all Properties

Material

Stone wool (Mineral Wool) ceiling tiles with factory applied latex paint on glass scrim surface
 ASTM E1264 CLASSIFICATION: Type XX - Stone wool base with membrane-faced overlay, Pattern G



Fire Performance

Surface burning characteristics:
 UL723 (ASTM E84) Flame Spread Index: 5
 Smoke Developed Index (UL Labeled): 0
 CAN/ULC S102 Flame Spread Index: 15
 Smoke Developed Index: 5



Environment

Up to 29% recycled content.
 Recycled content based on European manufacturing.



Thermal Insulation

R Value (BTU Units): 2.2 - 3.1
 RSI Value (Watts Units): 0.39 - 0.54



Sustainability

Many of Rockfon stone wool acoustic solutions are GREENGUARD Gold low VOC certified and meet the State of California's Department of Public Health Services Standard Practice for Specification Section 01350 (California Section 01350) for testing chemical emissions.

Selected potential applications: LEED, WELL, CHPS, Green Globes, BREEAM Int. and CALGreen.



Warranty

30-Year Limited Product Warranty.
 See rockfon.com



Hygiene

Stone wool provides no sustenance to microorganisms



Cleaning

- Vacuum



Greenguard Gold Certified for Office and Educational Environments

2019 | Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.
 © ROCKWOOL International A/S 2018. All rights reserved.
 ® denotes a trademark that is registered in the United States of America.

112619

Rockfon

4849 S. Austin Ave.
 Chicago, IL 60638 USA


Tel. +1-800-323-7164

Fax. +1-800-222-3744


rockfon.com

CITYTONES


STONE - 701
Light reflectance: 0.55




PLASTER - 702
Light reflectance: 0.58



GRAVEL - 703
Light reflectance: 0.34




MASTIC - 704
Light reflectance: 0.33




ZINC - 705
Light reflectance: 0.33



CONCRETE - 706
Light reflectance: 0.16



TARMAC - 707
Light reflectance: 0.13



Natural
tones

ANTHRACITE - 708
Light reflectance: 0.07



BLACK - 08
Light reflectance: 0.04




STUCCO - 720
Light reflectance: 0.70




CHALK - 721
Light reflectance: 0.51



LINEN - 722
Light reflectance: 0.29




HEMP - 723
Light reflectance: 0.45



CORK - 724
Light reflectance: 0.30




EARTH - 725
Light reflectance: 0.22



CLAY - 726
Light reflectance: 0.22




HUMUS - 727
Light reflectance: 0.05



The actual colour of the ceiling tiles may deviate slightly from printed colours due to the texture of the surface and the underlying colour of stone wool. Samples of the coloured surfaces are available upon request.

Sensorial TONES


LIGHT - 740
Light reflectance: 0.71




SUNRISE - 741
Light reflectance: 0.65



FRESH - 742
Light reflectance: 0.51




BREEZE - 743
Light reflectance: 0.45



AQUA - 744
Light reflectance: 0.25



MISTY - 745
Light reflectance: 0.60



TWILIGHT - 746
Light reflectance: 0.29



energetic tones

CHILI - 750
Light reflectance: 0.12



CURACAO - 751
Light reflectance: 0.22



VITAMIN - 752
Light reflectance: 0.46



PRECIOUS TONES

COPPER - 760
Light reflectance: 0.34



GOLD - 761
Light reflectance: 0.41



MERCURY - 762
Light reflectance: 0.44




Sophisticated tones

GARNET - 770
Light reflectance: 0.12



SCARLET - 771
Light reflectance: 0.08



ERMINE - 772
Light reflectance: 0.12



EMERALD - 773
Light reflectance: 0.07

