

DESIGNER™

Square Lay-in, Tegal coarse texture

UP TO **42%** RECYCLED CONTENT

Calculate LEED contribution at armstrongceilings.com/greengenie

LEED®

energy management
construction waste mgmt
regional materials
design for flexibility
EPD
recyclable/extended producer resp.
biobased materials
recycled content
sourcing of raw materials
material ingredient reporting
low emitting materials
lighting quality
acoustics

LOCATION DEPENDENT



Designer™ Lay-in panels with Prelude® 15/16" suspension system (Pgs. 391-392)

Designer™ panels offer a coarse-textured visual with standard absorption in an economical ceiling panel.

KEY SELECTION ATTRIBUTES

- Standard sound absorption
- Cost-effective

TYPICAL APPLICATIONS

- Utility rooms
- Discount stores
- Supply and storage rooms

COLOR



White
(WH)

VISUAL SELECTION

Edge Profile

Susp. Dwg.
Pgs. 407-411
armstrongceilings.com/catdwgs

Item No.

Dimensions (Inches)

DESIGNER Square Lay-in

15/16" Square Lay-in	1	735	24 x 24 x 5/8"	
	1	734	24 x 48 x 5/8"	

DESIGNER Tegal

15/16" Angled Tegal	13	737	24 x 24 x 5/8"	
---------------------	----	------------	----------------	--


¹ Total Acoustics® ceiling panels have an ideal combination of noise reduction and sound-blocking performance in one product.

PERFORMANCE SELECTION

Dots represent high level of performance.

UL Classified Acoustics			Total Acoustics ¹	Fire Performance	Light Reflect	Anti-Mold & Mildew	Sag Resist	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	Warranty
NRC	+	CAC										
0.55		30	–	Class A	0.81	–	Std	–	Std	Std	•	1-Yr
0.55		30	–	Class A	0.81	–	Std	–	Std	Std	•	1-Yr
0.55		33	–	Class A	0.81	–	Std	–	Std	Std	•	1-Yr

SUSPENSION SYSTEMS



PHYSICAL DATA

Material
Wet-formed mineral fiber

Surface Finish
Factory-applied latex paint

Fire Performance
Class A: Flame Spread Index 25 or less (UL labeled) per ASTM E1264

ASTM E1264 Classification
Type III, Form 2, Pattern F
Fire Class A

Humidity/Sag Resistance
Standard performance ceiling panels are recommended where the building is enclosed and the HVAC is continuously functioning.

Insulation Value
R Factor – 1.5 (BTU units)
R Factor – 0.26 (Watts units)

Warranty
Details at armstrongceilings.com

Weight; Square Feet/Carton
734 – 0.80 lbs/SF; 80 SF/ctn
735, 737 – 0.80 lbs/SF; 64 SF/ctn

Minimum Order Quantity
1 carton

Metric Items Available
735M, 734M, 737M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

TechLine / 1 877 276-7876
armstrongceilings.com/commercial
(search: designer)
BPCS-3024-517

LEED® is a registered trademark of the U.S. Green Building Council
UL is a registered trademark of UL LLC. All other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates
© 2016-2017 AWI Licensing LLC Printed in the United States of America

Armstrong®
CEILING & WALL SOLUTIONS

248

MINERAL FIBER