

# FISSURED™

## Square Lay-in & Tegular medium texture

UP TO **41%** RECYCLED CONTENT

Calculate LEED contribution at [armstrongceilings.com/greengenie](http://armstrongceilings.com/greengenie)

LEED®

energy management

construction waste mgmt

regional materials

design for flexibility

EPD

recyclable/extended producer resp.

biobased materials

recycled content

sourcing of raw materials

material ingredient reporting

low emitting materials

lighting quality

acoustics

LOCATION DEPENDENT



This economical panel with a directional, fissured visual offers standard acoustics.

### KEY SELECTION ATTRIBUTES

- Economical
- Directional fissured image

### TYPICAL APPLICATIONS

- Utility rooms
- Discount stores

### COLOR






### VISUAL SELECTION

Edge Profile	Susp. Dwg. Pgs. 407-411 <a href="http://armstrongceilings.com/catdwgs">armstrongceilings.com/catdwgs</a>	Item No.	Dimensions (Inches)	
<b>FISSURED™ Square Lay-in</b>				
	1	<b>756</b>	24 x 24 x 5/8"	
	1	<b>896</b>	24 x 24 x 5/8"	
	1	<b>755</b>	24 x 48 x 5/8"	
	1	<b>895</b>	24 x 48 x 5/8"	
	1	<b>Other Size Panels</b>	W: 12" – 30" / L: 18" – 72" 5/8" thick	
<b>FISSURED Tegular</b>				
	12	<b>705</b>	24 x 24 x 5/8"	
	12	<b>815</b>	24 x 24 x 5/8"	
	12	<b>Other Size Panels</b>	W: 12" – 30" / L: 18" – 72" 5/8" thick	


### PERFORMANCE SELECTION

Dots represent high level of performance.

UL Classified Acoustics		=	Total Acoustics <sup>1</sup>	Fire Performance 	Light Reflect	Anti-Mold & Mildew	Sag Resist	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program 	Warranty
NRC	+ CAC 											
0.55	30	–	Class A	0.81	–	Std	●	Std	Std	●	1-Yr	
0.55	35 ●	–	Fire Guard™	0.81	–	Std	●	Std	Std	●	1-Yr	
0.55	30	–	Class A	0.81	–	Std	●	Std	Std	●	1-Yr	
0.55	35 ●	–	Fire Guard	0.81	–	Std	●	Std	Std	●	1-Yr	
N/A	N/A	–	Class A	0.81	–	Std	●	Std	Std	●	1-Yr	
0.55	30	–	Class A	0.81	–	Std	●	Std	Std	●	1-Yr	
0.55	35 ●	–	Fire Guard	0.81	–	Std	●	Std	Std	●	1-Yr	
N/A	N/A	–	Class A	0.81	–	Std	●	Std	Std	●	1-Yr	

<sup>1</sup> Total Acoustics® ceiling panels have an ideal combination of noise reduction and sound-blocking performance in one product.

### SUSPENSION SYSTEMS



### PHYSICAL DATA

#### Material

Wet-formed mineral fiber

#### Surface Finish

Factory-applied latex paint

#### Fire Performance

ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less (UL labeled). Fire Guard™: A fire-resistive ceiling when used in applicable UL assemblies (Class A).

#### ASTM E1264 Classification

Type III, Form 2, Pattern C D  
Fire Class A

#### Humidity/Sag Resistance

Standard performance ceiling panels are recommended where the building is enclosed and the HVAC is continuously functioning.

#### VOC Emissions

Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010. This standard is the guideline for low emissions in LEED, CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

#### Insulation Value

755, 756, 895, 896 –  
R Factor – 1.5 (BTU units)  
R Factor – 0.26 (Watts units)

705, 815 –  
R Factor – 1.6 (BTU units)  
R Factor – 0.28 (Watts units)

#### Weight; Square Feet/Carton

705 – 0.69 lbs/SF; 64 SF/ctn  
755 – 0.66 lbs/SF; 96 SF/ctn  
756 – 0.67 lbs/SF; 64 SF/ctn  
815 – 1.08 lbs/SF; 48 SF/ctn  
895, 896 – 1.09 lbs/SF; 64 SF/ctn

#### Minimum Order Quantity

1 carton, excludes other size panels

#### Metric Items Available

756M, 896M, 755M, 895M, 705M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

TechLine / 1 877 276-7876  
[armstrongceilings.com/commercial](http://armstrongceilings.com/commercial)  
(search: fissured)  
BPCS-3030-517

LEED® is a registered trademark of the U.S. Green Building Council  
UL is a registered trademark of UL LLC. All other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates  
© 2016-2017 AWI Licensing LLC Printed in the United States of America

**Armstrong®**  
CEILING & WALL SOLUTIONS

262

MINERAL FIBER

