

GEORGIAN™ & GEORGIAN™ HIGH WASHABILITY

Square Lay-in & Tegular
medium texture



Georgian™ Beveled Tegular panels with Prelude® 15/16" suspension system (Pgs. 391-392)

This medium-textured panel offers good acoustics and high washability options to meet USDA/FSIS guidelines.

KEY SELECTION ATTRIBUTES

- Unique spatter-painted visual
- Total Acoustics® options (Items 795, 796)
- High Washability items available
 - Meets USDA/FSIS guidelines for use in food processing establishments
- Durable – Washable, Scrubbable, Impact-resistant, Scratch-resistant
- 30-Year Limited System Warranty against visible sag (excludes item 791 and other sizes), mold, and mildew

TYPICAL APPLICATIONS


- Schools/classrooms (Items 795, 796)
- Corridors/conference rooms
- Kitchen/food preparation areas (Items 793, 794)

COLOR



White (WH)

DETAILS (Other Suspension Systems compatible. Refer to listing on page 264.)



1. Georgian Beveled Tegular
2. Georgian Beveled Tegular with Prelude 15/16" suspension system
3. Georgian Beveled Tegular with Silhouette® 9/16" suspension system 1/4" Reveal

GEORGIAN™ & GEORGIAN™ HIGH WASHABILITY

Square Lay-in & Tegular medium texture

UP TO **56%** RECYCLED CONTENT

Calculate LEED contribution at armstrongceilings.com/greengenie

LEED®

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/extended producer resp.
- bio-based materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

LOCATION DEPENDENT

VISUAL SELECTION

Edge Profile	Susp. Dwg. Pgs. 407-411 armstrongceilings.com/cat/dwgs	Item No.	Dimensions (Inches)	
GEORGIAN™				
15/16" Square Lay-in	1	764	24 x 24 x 5/8"	
	1	763	24 x 48 x 5/8"	
	1	898	24 x 48 x 3/4"	
	1	791	30 x 60 x 3/4"	
15/16" Beveled Tegular	15	1752	24 x 24 x 5/8"	
9/16" Beveled Tegular	29, 44, 48, 52, 56	1753	24 x 24 x 5/8"	
SCHOOL ZONE® GEORGIAN				
15/16" Square Lay-in	1	796	24 x 24 x 3/4"	
	1	795	24 x 48 x 3/4"	
	1	Other Size Panels	W: 12" - 30" / L: 18" - 72" 3/4" Thick	
GEORGIAN – High Washability Panels, Unperforated				
15/16" Square Lay-in	1	794	24 x 24 x 5/8"	
	1	793	24 x 48 x 5/8"	


¹ Total Acoustics® ceiling panels have an ideal combination of noise reduction and sound-blocking performance in one product.
GOOD (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)

PERFORMANCE SELECTION

Dots represent high level of performance.

UL Classified Acoustics	NRC + CAC	=	Total Acoustics ¹	Fire Performance	Light Reflect	Anti-Mold & Mildew	Sag Resist	Certified Low VOC Emissions	Wash	Scrub	Impact	Scratch	Recycled Content	Recycle Program	30-Yr Warranty	Durability	
																	Class A
0.55	33	–	Class A	0.86	•	•	•	•	•	•	•	•	•	•	•	•	•
0.55	33	–	Class A	0.86	•	•	•	•	•	•	•	•	•	•	•	•	•
0.55	35	–	Fire Guard™	0.86	•	•	•	•	•	•	•	•	•	•	•	•	•
0.55	33	–	Class A	0.86	•	•	Std	•	•	•	•	•	•	•	•	•	1-Yr
0.55	35	–	Class A	0.86	•	•	•	•	•	•	•	•	•	•	•	•	•
0.65	35	GOOD	Class A	0.86	•	•	•	•	•	•	•	•	•	•	•	•	•
0.65	35	GOOD	Class A	0.86	•	•	•	•	•	•	•	•	•	•	•	•	•
N/A	N/A	–	Class A	0.86	•	•	Std	•	•	•	•	•	•	•	•	•	1-Yr
N/A	33	–	Class A	0.88	•	•	•	•	•	•	•	•	•	•	•	•	•
N/A	33	–	Class A	0.88	•	•	•	•	•	•	•	•	•	•	•	•	•

SUSPENSION SYSTEMS



PHYSICAL DATA

Material

Wet-formed mineral fiber

Surface Finish

Factory-applied latex paint

Fire Performance

ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less (UL labeled). Fire Guard™: A fire-resistive ceiling when used in applicable UL assemblies (Class A).

ASTM E1264 Classification

Type III, Form 2, Pattern C E
 Items 794, 793, 898 –
 Type IX, Form 2, Pattern G
 Fire Class A

Sag Resistance

HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not

including, standing water and outdoor applications. Excludes Item 791 and other size panels.

Mold/Mildew Protection

Ceiling panels with BioBlock® performance resist the growth of mold and mildew.

Acoustical Performance

CAC testing conducted using Silhouette® suspension system.

VOC Emissions

Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010. This standard is the guideline for low emissions in LEED, CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

High Recycled Content

Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Insulation Value

R Factor - 1.6 (BTU units)
 R Factor - 0.28 (Watts units)

30-Year Performance Guarantee & Warranty

When installed with Armstrong® Suspension System. Details at armstrongceilings.com

Weight; Square Feet/Carton

763, 793 – 0.67 lbs/SF; 96 SF/ctn
 764, 794, 1752, 1753 – 0.72 lbs/SF; 64 SF/ctn
 791 – 0.76 lbs/SF; 75 SF/ctn
 898 – 1.13 lbs/SF; 64 SF/ctn
 796 – 1.31 lbs/SF; 48 SF/ctn
 795 – 1.38 lbs/SF; 64 SF/ctn

Minimum Order Quantity

1 carton, excludes other size panels

Metric Items Available

1753M, 764M, 763M, 791M, 1752M, 796M, 795M, 794M, 793M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.



MINERAL FIBER