

USG HALCYON™ PLANKS AND LARGE SIZE ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

USG Halcyon™ Acoustical Planks
with ClimaPlus™ Performance/
USG Donn® Brand Centricitee™ DXT™
Acoustical Suspension System

TO ORDER SAMPLES, GO TO USG.COM OR CGCINC.COM



Flat White
050

FEATURES AND BENEFITS

- Exceptional noise reduction with NRC values up to 1.00 and AC values up to 200 for open-plan offices.
- High light-reflective finish (LR-0.90) reduces light fixtures and energy use.
- Washable and scrubbable finish.
- Impact and scratch resistant.
- Coordinates visually with USG Mars™ Acoustical Panels for open- or closed-plan applications.
- Compatible with USG Logix™ Integrated Ceiling Systems.
- Nondirectional, monolithic visual reduces installation time and waste.
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.
- Balanced Acoustic options with Foil-Backed products.

APPLICATIONS

- Open-plan areas
- Areas with indirect lighting
- Corridors
- Convention halls and concourses
- Reception and lobby areas
- Libraries

SUBSTRATE

- Fiberglass

Fine-Textured Panel

USG HALCYON™ PLANKS AND LARGE SIZE ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE



ORDER SAMPLES/LITERATURE
USG: samplitt@usg.com
fax: 888.874.2348 | usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE TECHNICAL INFORMATION AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com

TECHNICAL SERVICES
800 USG.4YOU (874-4968)

UL Classified

Edge	Panel Size ²	Fire Rating	Item No.	NRC	CAC Min.	LR	Color	Grid Options	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
SQ 	2'x5'x3/4"	Class A	99282	0.90	20	0.90	White	A,B		38%	\$\$\$\$
	2'x6'x3/4"	Class A	97262	0.90	20	0.90	White	A,B		38%	\$\$\$\$
	2'x8'x3/4"	Class A	97263	0.90	20	0.90	White	A,B		38%	\$\$\$\$
	2'x5'x1"	Class A	99262	0.90	20	0.90	White	A,B		40%	\$\$\$\$
SL 	2'x6'x1"	Class A	99268	0.95	20	0.90	White	C		40%	\$\$\$\$
	2'x6'x1" Foil-Back	Class A	97360	0.90	30	0.90	White	C		40%	\$\$\$\$\$
	2'x8'x1"	Class A	99269	0.95	20	0.90	White	C		40%	\$\$\$\$
	2'x8'x1" Foil-Back	Class A	97361	0.90	30	0.90	White	C		40%	\$\$\$\$\$
FL 	2'x6'x1"	Class A	98348	0.95	20	0.90	White	D,E,F,G		40%	\$\$\$\$
	2'x6'x1" Foil-Back	Class A	97362	0.90	30	0.90	White	D,E,F,G		40%	\$\$\$\$\$
	2'x8'x1"	Class A	98197	0.95	20	0.90	White	D,E,F,G		40%	\$\$\$\$
	2'x8'x1" Foil-Back	Class A	97367	0.90	30	0.90	White	D,E,F,G		40%	\$\$\$\$\$
SQ 	4'x4'x1"	Class A	98441	0.95	20	0.90	White	A,B		40%	\$\$\$\$
	4'x4'x1" Foil-Back	Class A	97363	0.90	30	0.90	White	A,B		40%	\$\$\$\$\$
	4'x8'x1"	Class A	98481	0.95	20	0.90	White	A,B		40%	\$\$\$\$
	4'x8'x1" Foil-Back	Class A	97364	0.90	30	0.90	White	A,B		40%	\$\$\$\$\$
SL 	4'x4'x1"	Class A	98443	0.95	20	0.90	White	C		40%	\$\$\$\$
	4'x4'x1" Foil-Back	Class A	97365	0.90	30	0.90	White	C		40%	\$\$\$\$\$
FL 	4'x4'x1"	Class A	98445	0.95	20	0.90	White	D,E,F,G		40%	\$\$\$\$
	4'x4'x1" Foil-Back	Class A	97366	0.90	30	0.90	White	D,E,F,G		40%	\$\$\$\$\$

ClimaPlus™ Warranty Performance⁴

Fiberglass substrate is inherently resistant to the growth of mold and mildew. Includes sag-resistance performance.

GRID PROFILE OPTIONS

A USG DX [®] /DXL™	B USG DXW™	C USG DX [®] /DXL™	D USG Centricitee™	E USG Finline [®] DXF™	F USG Finline [®] 1/8 DXFF™	G USG Identitee [®] DXI™
<p>Use to stabilize grid installation without cross tees. Use in large module applications.</p>					ASB24 24" Stabilizer Bar ASB30 30" Stabilizer Bar ASB48 48" Stabilizer Bar	

PHYSICAL DATA/ FOOTNOTES

Notice

The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC2483/rev. 11-16

© 2016 USG Corporation and/or its affiliates. All rights reserved. Printed in U.S.A.

Product literature
Data sheet: SC2483

ASTM E1264 classification
Type XII, Form 2, Pattern E & G

ASTM E84 and CAN/ULC S102 surface-burning characteristics
Class A
Flame spread: 25 or less
Smoke developed: 50 or less

Weight
0.38 lb./sq. ft. (3/4" panels)
0.47 lb./sq. ft. (1" panels)

Online tools
usgdesignstudio.com or cgcdesignstudio.com

Thermal resistance
R-3.3 (3/4" panels)
R-4.4 (1" panels)

Maximum backloading
See *USG 30-Year Limited Warranty Commercial Applications* (SC2102).

Maintenance
Can be cleaned easily with a soft brush or vacuum.
To clean panel, use a clean, white cloth with water or a mild detergent and wipe surface.

Metric sizes available
Contact sales for minimum quantities and lead times.

Treating field-cut reveal edges
All field-cut edges "exposed to view" should be colored to match the factory finish. USG Halcyon™ Touch-up Edge Paint is recommended when perimeter field cuts expose the yellow substrate.

Notes

- For details, see LEED report tool at usgdesignstudio.com or [Plank and Large Panel Stabilizer Bars Application Guide \(IC592\).](http://cgcdesignstudio.com.
Custom-size panels available. Please contact your USG sales representative for details.
Stabilizer bar recommended if opening ≥ 48)
- For details, see *USG 30-Year Limited Warranty Commercial Applications* (SC2102) and *ClimaPlus™ Ceilings Certification of Performance* (SC2451).

Manufactured by
USG Interiors, LLC
550 West Adams Street
Chicago, IL 60661

The trademarks USG, CGC, CENTRICITEE, CLIMAPLUS, DONN, DX, DXF, DXFF, DXI, DXL, DXT, DXW, FINELINE, HALCYON, IDENTITEE, LOGIX, MARS, IT'S YOUR WORLD, BUILD IT, the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

