


| Available Sizes & Lengths |        |         |
|---------------------------|--------|---------|
| Stock #                   | Length | Pcs/box |
| 2710                      | 10'    | 25      |



## Product(s): Hideaway Expansion Bead

**Description:** Hideaway Expansion Bead from Trim-Tex features a coextruded flexible PVC center that is designed to provide a full <sup>3</sup>/<sup>8</sup> of protection against the stresses of expansion and contraction.

**Advantages:** Made from rust proof, dent resistant PVC to reduce jobsite and handling damage. Features a unique masking system comprised of tear away fins that protect the center from drywall compound and provide a cleaner, sharper finish than removable tape masking systems.

**Limitations:** Hideaway Expansion is not a fire stop. For fire rated applications, an approved fire backer must be placed behind the bead. Check local codes or architectural specs. Hideaway Expansion must be painted with a high quality paint, especially in exterior applications.

**Applicable Standards:** Rigid PVC products made by Trim-Tex meet ASTM specifications D3678-97, D1784-03, C1047-99.

**Surface Characteristics:** Trim-Tex products are made from PVC. PVC does not support combustion and is self extinguishing when the source of flame or heat is removed.

**Installation:** For long runs, it may be helpful to snap a chalk line as a guide for the Hideaway Expansion. To install the bead, cut the bead to length. Spray the bead and then the drywall with Trim-Tex 847 Spray Adhesive. Immediately apply to the drywall. Staple both legs every 6"-8" with 1/2" long divergent staples. Detailed installation instructions are included with each of the product

**Finishing**: For the ultimate performance, brush in the center of the Hideaway with an exterior acrylic semi-gloss paint. Always use high quality paints as they bond better and have more flexibility than more inexpensive brands. Do not prime the flexible center of the Hideaway. If applying primer by spray, try not to spray any primer into the flexible center. The heavier the paint is applied, the worse the paint will perform. Brush in a coat of the final paint color.

Accessories: 847 Spray Adhesive, Staple Guns and Divergent Staples, Trim-Tex Sanding Blocks & Abrasive Products, Mud-Max Drywall Compound Additive, North Safety Products distributed by Trim-Tex.

Job Name

Contractor\_\_\_\_\_Date\_\_\_\_ Approvals (Signatures or Stamps)