

Rockfon® Industrial™ Nature

FEATURES & BENEFITS

- For industrial applications
- Excellent sound absorption (NRC = 1.05)
- High fire performance
- To create a new ceiling or place under an existing one
- Available in white, natural and black finish
- Available in square lay-in

APPLICATIONS

- Light Industry
- Heavy Industry





Rockfon® Industrial™ Nature















Edge designation	ltem number	Modular size (nominal)	lbs/ sqft	sqft/ carton	NRC	CAC	AC	Fire Class	Light Reflectance	Sag resistance (relative humidity)	LOW VOC
Square Lay In SQ	6200	2′ x 4′ x 2″	0.80	32	1.05	22	-	А	0.40	UPTO 100%	√

MATERIAL

Stone wool (Mineral Wool) ceiling tiles with factory painted glass scrim surface

ASTM E1264 CLASSIFICATION: Type XX - Stone wool base with membrane-faced overlay, Pattern G



FIRE PERFORMANCE:

Surface burning characteristics:

UL723 (ASTM E84) Flame Spread Index: 0 Smoke Developed Index (UL Labeled): 5 CAN/ULC S102 Flame Spread Index: 5 Smoke Developed Index: 0



ENVIRONMENT

Fully recyclable



THERMAL INSULATION

R Value (BTU Units): 7.0 RSI Value (Watts Units): 1.23



VOC/FORMALDEHYDE EMISSIONS

All Rockfon stone wool acoustic solutions are GREENGUARD Gold low VOC certified and meet the State of California's Department of Public Health Services Standard Practice for Specification Section 01350 (California Section 01350) for testing chemical emissions.

Selected potential applications: LEED, WELL, CHPS, Green Globes, BREEAM Int. and CALGreen.



WARRANTY INFORMATION:

30-Year Limited Product Warranty. See www.rockfon.com



HYGIENE

Stone wool provides no sustenance to microorganisms



CLEANING

Vacuum

15/16" SUSPENSION SYSTEMS	9/16" SUSPENSION SYSTEMS				
1200, 200 and Fire rated systems	4000 and Fire rated systems				
sa					