

# KITCHEN ZONE™

Square Lay-in  
smooth texture



Kitchen Zone™ 24" x 24" panels with Prelude® 15/16" suspension system (Pgs. 391-392)

A better option to vinyl-covered gypsum, this panel offers a lower cost, lighter weight, more pieces per carton, and meets USDA/FSIS guidelines.

## KEY SELECTION ATTRIBUTES

- Easier to cut with less dust
- Recyclable through Armstrong® Recycling Program
- Brighter visual with 20% more light reflectance than vinyl-covered gypsum
- Durable – Water-repellent, Washable, Scratch-resistant, Soil-resistant
- Smooth surface meets USDA/FSIS guidelines for use in food processing areas
- 30-Year Limited System Warranty against visible sag, mold, and mildew

## TYPICAL APPLICATIONS


- Kitchen/food preparation areas
- Laboratories
- Cafeterias
- Lavatories/restrooms

## COLOR




White  
(WH)

## DETAILS



1



2

1. Kitchen Zone™ Lay-in
2. Kitchen Zone Lay-in with Prelude® 15/16" suspension system

# KITCHEN ZONE™




Square Lay-in  
smooth texture

UP TO **36%** RECYCLED CONTENT

Calculate LEED contribution at [armstrongceilings.com/greengenie](http://armstrongceilings.com/greengenie)

- LEED®
- energy management
- construction waste to reuse
- regional materials
- design for flexibility
- EPD
- recyclable/extended producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

## VISUAL SELECTION

Edge Profile	Susp. Dwg. Pgs. 407-411 <a href="http://armstrongceilings.com/catdwgs">armstrongceilings.com/catdwgs</a>	Item No.	Dimensions (Inches)
<b>KITCHEN ZONE™</b>			
15/16" Square Lay-in 	1	<b>673</b>	24 x 24 x 5/8" 
	1	<b>672</b>	24 x 48 x 5/8" 

## PERFORMANCE SELECTION

Dots represent high level of performance.




NRC	+ CAC	=	Total Acoustics <sup>1</sup>	Fire Performance	Light Reflect	Anti-Mold & Mildew	Sag Resist	Certified Low VOC Emissions	Water Repel	Wash	Scratch	Soil	Recycled Content	Recycle Program	30-Yr Warranty
N/A	33	-	Class A	0.89	•	•	•	-	•	•	•	•	Std	•	•
N/A	33	-	Class A	0.89	•	•	•	-	•	•	•	•	Std	•	•

*Note: Durability icons (Water Repel, Wash, Scratch, Soil) are grouped under a bracket labeled 'Durability'.*

<sup>1</sup> Total Acoustics® ceiling panels have an ideal combination of noise reduction and sound-blocking performance in one product.

## SUSPENSION SYSTEMS

15/16"



## PHYSICAL DATA

### Material

Wet-formed mineral fiber

### Surface Finish

Factory-applied latex paint

### Fire Performance

ASTM E84 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less.

### ASTM E1264 Classification

Type IX, Form 2, Pattern G  
Fire Class A

### Humidity/Sag Resistance

HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

### Mold/Mildew Protection

Ceiling panels with BioBlock® performance resist the growth of mold and mildew.

### Insulation Value

R Factor – 1.6 (BTU units)  
R Factor – 0.28 (Watts units)

### Application Consideration

Not designed for use in close proximity to commercial grease ducts.

### 30-Year Performance Guarantee & Warranty

When installed with Armstrong® Suspension System. Details at [armstrongceilings.com](http://armstrongceilings.com)

### Cleaning Recommendations

To clean panel, use a clean, white cloth with water or a mild detergent and wipe surface. To disinfect panel, lightly spray surface and wipe clean with a clean, white cloth. Acceptable colorless disinfectants include:

- Sodium hypochlorite
- Hydrogen peroxide
- Quaternary ammonium

### Weight; Square Feet/Carton

672 – 0.67 lbs/SF; 96 SF/ctn  
673 – 0.82 lbs/SF; 64 SF/ctn

### Minimum Order Quantity

1 carton