

USG MARS™/MARS™ HIGH-NRC LOGIX™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER

USG Mars™ Acoustical Panels with
SQ Edge/USG Donn® Brand DX*/DXL™
Acoustical Suspension System

Photo this page:
© Andrew Latreille
Architects: Perkins+Will/KRA/Group2

TO ORDER SAMPLES,
GO TO USG.COM OR CGCINC.COM



Flat White
050

Fine-Textured Panel

FEATURES AND BENEFITS

- Compatible with USG Logix™ Integrated System.
- Monolithic, structured ceiling visual using standard components.
- High light-reflective finish (LR-0.90) reduces light fixtures and energy use.
- Washable and scrubbable finish—impact and scratch resistant.
- Coordinates visually with USG Halcyon™ Logix™ Acoustical Panels for open/closed-plan applications.
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.
- GREENGUARD Gold Certified for low-emitting performance.
- Balanced Acoustics. High-NRC and High-CAC.

APPLICATIONS

- Open-plan offices
- Conference rooms
- Reception and lobby areas
- Media centers and libraries
- Airports
- Spaces with indirect or natural lighting

SUBSTRATE

- Wet-formed mineral fiber

USG MARS™/MARS™ HIGH-NRC LOGIX™ ACOUSTICAL PANELS 75/35

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER


ORDER SAMPLES/LITERATURE
USG: samplitt@usg.com
fax: 888 874-2348 | usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com

TECHNICAL SERVICES
800 USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
ULCOM/CG
UL2818



UL Classified

Edge	Panel Size ⁵	Fire Rating	Item No.	NRC	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
SQ <input type="checkbox"/>	20"x54"x3/4"	Class A	86519	0.75	35	0.90	White	A	Low		69%	\$\$
	20"x56"x3/4"	Class A	86520	0.75	35	0.90	White	A	Low		69%	\$\$
	20"x60"x3/4"	Class A	86160	0.75	35	0.90	White	A	Low		69%	\$\$
	21"x24"x3/4"	Class A	86522	0.75	35	0.90	White	A, B	Low		69%	\$\$
	21"x48"x3/4"	Class A	86523	0.75	35	0.90	White	A	Low		69%	\$\$
	22"x24"x3/4"	Class A	86524	0.75	35	0.90	White	A, B	Low		69%	\$\$
	22"x48"x3/4"	Class A	86525	0.75	35	0.90	White	A	Low		69%	\$\$
	24"x24"x3/4"	Class A	86185	0.75	35	0.90	White	A, B	Low		69%	\$\$
	24"x42"x3/4"	Class A	86527	0.75	35	0.90	White	A	Low		69%	\$\$
	24"x44"x3/4"	Class A	86528	0.75	35	0.90	White	A	Low		69%	\$\$
	24"x48"x3/4"	Class A	88185	0.75	35	0.90	White	A	Low		69%	\$\$
	24"x72"x3/4"	Class A	86223	0.75	35	0.90	White	A	Low		69%	\$\$
	27"x30"x3/4"	Class A	86530	0.75	35	0.90	White	A	Low		69%	\$\$
	27"x60"x3/4"	Class A	86531	0.75	35	0.90	White	A	Low		69%	\$\$
	28"x30"x3/4"	Class A	86532	0.75	35	0.90	White	A	Low		69%	\$\$
	28"x60"x3/4"	Class A	86533	0.75	35	0.90	White	A	Low		69%	\$\$
	30"x30"x3/4"	Class A	86815	0.75	35	0.90	White	A	Low		69%	\$\$
	30"x54"x3/4"	Class A	86503	0.75	35	0.90	White	A	Low		69%	\$\$
	30"x56"x3/4"	Class A	86535	0.75	35	0.90	White	A	Low		69%	\$\$
	30"x60"x3/4"	Class A	86536	0.75	35	0.90	White	A	Low		69%	\$\$
SQ <input type="checkbox"/>	4"x48"x3/4"	Class A	86514	0.75	35	0.90	White	A	Low		69%	\$\$
	4"x60"x3/4"	Class A	86515	0.75	35	0.90	White	A	Low		69%	\$\$
	4"x72"x3/4"	Class A	86537	0.75	35	0.90	White	A	Low		69%	\$\$
	6"x48"x3/4"	Class A	86325	0.75	35	0.90	White	A	Low		69%	\$\$
	6"x60"x3/4"	Class A	86507	0.75	35	0.90	White	A	Low		69%	\$\$
	6"x72"x3/4"	Class A	86538	0.75	35	0.90	White	A	Low		69%	\$\$
	12"x12"x3/4"	Class A	86134	0.75	35	0.90	White	A	Low		69%	\$\$
	12"x24"x3/4"	Class A	86289	0.75	35	0.90	White	A	Low		69%	\$\$
	12"x48"x3/4"	Class A	86516	0.75	35	0.90	White	A	Low		69%	\$\$
	12"x60"x3/4"	Class A	86517	0.75	35	0.90	White	A	Low		69%	\$\$
12"x72"x3/4"	Class A	86518	0.75	35	0.90	White	A	Low		69%	\$\$	

Low Emissions (VOC)
Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.1 - 2010 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at productguide.ulenvironment.com.

ClimaPlus™ Warranty Performance³
Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content
Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

USG MARS™ LOGIX™
FIELD PANELS
75/35

USG MARS™ LOGIX™
CHANNEL PANELS
75/35

USG MARS™/MARS™ HIGH-NRC LOGIX™ ACOUSTICAL PANELS 75/35

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER


ORDER SAMPLES/LITERATURE
USG: samplit@usg.com
fax: 888 874-2348 | usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com

TECHNICAL SERVICES
800 USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
ULCOM/GG
UL2818



USG MARS™ LOGIX™ FIELD PANELS 75/35

USG MARS™ LOGIX™ CHANNEL PANELS 75/35

Edge	Panel Size ⁵	Fire Rating	Item No.	UL Classified		LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
				NRC	CAC Min.							
SLT	20"x54"x3/4"	Class A	86547	0.75	35	0.90	White	C	Low	69%	\$\$	
	20"x56"x3/4"	Class A	86548	0.75	35	0.90	White	C	Low	69%	\$\$	
	20"x60"x3/4"	Class A	86905	0.75	35	0.90	White	C	Low	69%	\$\$	
	21"x24"x3/4"	Class A	86550	0.75	35	0.90	White	C	Low	69%	\$\$	
	21"x48"x3/4"	Class A	86551	0.75	35	0.90	White	C	Low	69%	\$\$	
	22"x24"x3/4"	Class A	86552	0.75	35	0.90	White	C	Low	69%	\$\$	
	22"x48"x3/4"	Class A	86553	0.75	35	0.90	White	C	Low	69%	\$\$	
	24"x24"x3/4"	Class A	86785	0.75	35	0.90	White	C	Low	69%	\$\$	
	24"x42"x3/4"	Class A	86555	0.75	35	0.90	White	C	Low	69%	\$\$	
	24"x44"x3/4"	Class A	86556	0.75	35	0.90	White	C	Low	69%	\$\$	
	24"x48"x3/4"	Class A	88785	0.75	35	0.90	White	C	Low	69%	\$\$	
	24"x72"x3/4"	Class A	86166	0.75	35	0.90	White	C	Low	69%	\$\$	
	27"x30"x3/4"	Class A	86557	0.75	35	0.90	White	C	Low	69%	\$\$	
	27"x60"x3/4"	Class A	86558	0.75	35	0.90	White	C	Low	69%	\$\$	
	28"x30"x3/4"	Class A	86559	0.75	35	0.90	White	C	Low	69%	\$\$	
	28"x60"x3/4"	Class A	86560	0.75	35	0.90	White	C	Low	69%	\$\$	
	30"x30"x3/4"	Class A	86875	0.75	35	0.90	White	C	Low	69%	\$\$	
	30"x54"x3/4"	Class A	88686	0.75	35	0.90	White	C	Low	69%	\$\$	
	30"x56"x3/4"	Class A	86563	0.75	35	0.90	White	C	Low	69%	\$\$	
	30"x60"x3/4"	Class A	86564	0.75	35	0.90	White	C	Low	69%	\$\$	
SLT	4"x48"x3/4"	Class A	86540	0.75	35	0.90	White	C	Low	69%	\$\$	
	4"x60"x3/4"	Class A	86541	0.75	35	0.90	White	C	Low	69%	\$\$	
	4"x72"x3/4"	Class A	86565	0.75	35	0.90	White	C	Low	69%	\$\$	
	6"x48"x3/4"	Class A	86542	0.75	35	0.90	White	C	Low	69%	\$\$	
	6"x60"x3/4"	Class A	86543	0.75	35	0.90	White	C	Low	69%	\$\$	
	6"x72"x3/4"	Class A	86566	0.75	35	0.90	White	C	Low	69%	\$\$	
	12"x12"x3/4"	Class A	86135	0.75	35	0.90	White	C	Low	69%	\$\$	
	12"x24"x3/4"	Class A	86245	0.75	35	0.90	White	C	Low	69%	\$\$	
	12"x48"x3/4"	Class A	86544	0.75	35	0.90	White	C	Low	69%	\$\$	
	12"x60"x3/4"	Class A	86545	0.75	35	0.90	White	C	Low	69%	\$\$	
	12"x72"x3/4"	Class A	86546	0.75	35	0.90	White	C	Low	69%	\$\$	

Low Emissions (VOC)
Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.1 - 2010 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at productguide.ulenvironment.com.

ClimaPlus™ Warranty Performance³
Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content
Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

USG MARS™/MARS™ HIGH-NRC LOGIX™ ACOUSTICAL PANELS 75/35

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER


ORDER SAMPLES/LITERATURE
USG: samplitt@usg.com
fax: 888 874-2348 | usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com

TECHNICAL SERVICES
800 USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
ULCOM/GG
UL2818



UL Classified

Edge	Panel Size ⁵	Fire Rating	Item No.	NRC	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
FLB	20"x54"x3/4"	Class A	88845	0.75	35	0.90	White	D,E,F	Low		69%	\$\$
	20"x56"x3/4"	Class A	86571	0.75	35	0.90	White	D,E,F	Low		69%	\$\$
	20"x60"x3/4"	Class A	86164	0.75	35	0.90	White	D,E,F	Low		69%	\$\$
	21"x24"x3/4"	Class A	88840	0.75	35	0.90	White	D,E,F	Low		69%	\$\$
	21"x48"x3/4"	Class A	86573	0.75	35	0.90	White	D,E,F	Low		69%	\$\$
	22"x24"x3/4"	Class A	86574	0.75	35	0.90	White	D,E,F	Low		69%	\$\$
	22"x48"x3/4"	Class A	86575	0.75	35	0.90	White	D,E,F	Low		69%	\$\$
	24"x24"x3/4"	Class A	86985	0.75	35	0.90	White	D,E,F	Low		69%	\$\$
	24"x42"x3/4"	Class A	86577	0.75	35	0.90	White	D,E,F	Low		69%	\$\$
	24"x44"x3/4"	Class A	86578	0.75	35	0.90	White	D,E,F	Low		69%	\$\$
	24"x48"x3/4"	Class A	88985	0.75	35	0.90	White	D,E,F	Low		69%	\$\$
	24"x72"x3/4"	Class A	88996	0.75	35	0.90	White	D,E,F	Low		69%	\$\$
	27"x30"x3/4"	Class A	86850	0.75	35	0.90	White	D,E,F	Low		69%	\$\$
	27"x60"x3/4"	Class A	86579	0.75	35	0.90	White	D,E,F	Low		69%	\$\$
	28"x30"x3/4"	Class A	86834	0.75	35	0.90	White	D,E,F	Low		69%	\$\$
	28"x60"x3/4"	Class A	86580	0.75	35	0.90	White	D,E,F	Low		69%	\$\$
	30"x30"x3/4"	Class A	86830	0.75	35	0.90	White	D,E,F	Low		69%	\$\$
	30"x54"x3/4"	Class A	86831	0.75	35	0.90	White	D,E,F	Low		69%	\$\$
	30"x56"x3/4"	Class A	86583	0.75	35	0.90	White	D,E,F	Low		69%	\$\$
	30"x60"x3/4"	Class A	86267	0.75	35	0.90	White	D,E,F	Low		69%	\$\$
FLB	4"x48"x3/4"	Class A	86568	0.75	35	0.90	White	D,E,F	Low		69%	\$\$
	4"x60"x3/4"	Class A	86569	0.75	35	0.90	White	D,E,F	Low		69%	\$\$
	4"x72"x3/4"	Class A	86584	0.75	35	0.90	White	D,E,F	Low		69%	\$\$
	6"x48"x3/4"	Class A	88887	0.75	35	0.90	White	D,E,F	Low		69%	\$\$
	6"x60"x3/4"	Class A	86835	0.75	35	0.90	White	D,E,F	Low		69%	\$\$
	6"x72"x3/4"	Class A	86567	0.75	35	0.90	White	D,E,F	Low		69%	\$\$
	12"x12"x3/4"	Class A	86136	0.75	35	0.90	White	D,E,F	Low		69%	\$\$
	12"x24"x3/4"	Class A	86242	0.75	35	0.90	White	D,E,F	Low		69%	\$\$
	12"x48"x3/4"	Class A	86321	0.75	35	0.90	White	D,E,F	Low		69%	\$\$
	12"x60"x3/4"	Class A	88885	0.75	35	0.90	White	D,E,F	Low		69%	\$\$
	12"x72"x3/4"	Class A	86570	0.75	35	0.90	White	D,E,F	Low		69%	\$\$

Low Emissions (VOC)
Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.1 - 2010 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at productguide.ulenvironment.com.

ClimaPlus™ Warranty Performance³
Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content
Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

USG MARS™/MARS™ HIGH-NRC LOGIX™ ACOUSTICAL PANELS 80/35

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER

ORDER SAMPLES/LITERATURE
USG: samplit@usg.com
fax: 888.874.2348 | usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com

TECHNICAL SERVICES
800 USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
ULCOM/GG
UL2818



UL Classified

Edge	Panel Size ⁵	Fire Rating	Item No.	NRC	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
SQ <input type="checkbox"/>	20"x54"x7/8"	Class A	86410	0.80	35	0.90	White	A	Low		70%	\$\$
	20"x56"x7/8"	Class A	86411	0.80	35	0.90	White	A	Low		70%	\$\$
	20"x60"x7/8"	Class A	89501	0.80	35	0.90	White	A	Low		70%	\$\$
	21"x24"x7/8"	Class A	86414	0.80	35	0.90	White	A, B	Low		70%	\$\$
	21"x48"x7/8"	Class A	86415	0.80	35	0.90	White	A	Low		70%	\$\$
	22"x24"x7/8"	Class A	86416	0.80	35	0.90	White	A, B	Low		70%	\$\$
	22"x48"x7/8"	Class A	86417	0.80	35	0.90	White	A	Low		70%	\$\$
	24"x24"x7/8"	Class A	86100	0.80	35	0.90	White	A, B	Low		70%	\$\$
	24"x42"x7/8"	Class A	86419	0.80	35	0.90	White	A	Low		70%	\$\$
	24"x44"x7/8"	Class A	86420	0.80	35	0.90	White	A	Low		70%	\$\$
	24"x48"x7/8"	Class A	86300	0.80	35	0.90	White	A	Low		70%	\$\$
	24"x72"x7/8"	Class A	86360	0.80	35	0.90	White	A	Low		70%	\$\$
	27"x30"x7/8"	Class A	86421	0.80	35	0.90	White	A	Low		70%	\$\$
	27"x60"x7/8"	Class A	86422	0.80	35	0.90	White	A	Low		70%	\$\$
	28"x30"x7/8"	Class A	86423	0.80	35	0.90	White	A	Low		70%	\$\$
	28"x60"x7/8"	Class A	86424	0.80	35	0.90	White	A	Low		70%	\$\$
	30"x30"x7/8"	Class A	86426	0.80	35	0.90	White	A	Low		70%	\$\$
	30"x54"x7/8"	Class A	86427	0.80	35	0.90	White	A	Low		70%	\$\$
	30"x56"x7/8"	Class A	86428	0.80	35	0.90	White	A	Low		70%	\$\$
	30"x60"x7/8"	Class A	86429	0.80	35	0.90	White	A	Low		70%	\$\$
SQ <input type="checkbox"/>	4"x60"x7/8"	Class A	86403	0.80	35	0.90	White	A	Low		70%	\$\$
	4"x72"x7/8"	Class A	86405	0.80	35	0.90	White	A	Low		70%	\$\$
	6"x48"x7/8"	Class A	86404	0.80	35	0.90	White	A	Low		70%	\$\$
	6"x60"x7/8"	Class A	86145	0.80	35	0.90	White	A	Low		70%	\$\$
	6"x72"x7/8"	Class A	86406	0.80	35	0.90	White	A	Low		70%	\$\$
	12"x48"x7/8"	Class A	86407	0.80	35	0.90	White	A	Low		70%	\$\$
	12"x60"x7/8"	Class A	86408	0.80	35	0.90	White	A	Low		70%	\$\$
	12"x72"x7/8"	Class A	86409	0.80	35	0.90	White	A	Low		70%	\$\$

Low Emissions (VOC)
Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.1 - 2010 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at productguide.ulenvironment.com.

ClimaPlus™ Warranty Performance³
Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content
Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

USG MARS™ HIGH-NRC
LOGIX™ FIELD PANELS
80/35

Plant-Based Binder

USG MARS™ HIGH-NRC
LOGIX™ CHANNEL PANELS
80/35

Plant-Based Binder

USG MARS™/MARS™ HIGH-NRC LOGIX™ ACOUSTICAL PANELS 80/35

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER

ORDER SAMPLES/LITERATURE
USG: samplitt@usg.com
fax: 888 874-2348 | usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com

TECHNICAL SERVICES
800 USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
ULCOM/GG
UL2818



UL Classified

Edge	Panel Size ⁵	Fire Rating	Item No.	NRC	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
SLT	20"x54"x7/8"	Class A	86447	0.80	35	0.90	White	C	Low		70%	\$\$
	20"x56"x7/8"	Class A	86448	0.80	35	0.90	White	C	Low		70%	\$\$
	20"x60"x7/8"	Class A	86449	0.80	35	0.90	White	C	Low		70%	\$\$
	21"x24"x7/8"	Class A	86451	0.80	35	0.90	White	C	Low		70%	\$\$
	21"x48"x7/8"	Class A	86452	0.80	35	0.90	White	C	Low		70%	\$\$
	22"x24"x7/8"	Class A	86453	0.80	35	0.90	White	C	Low		70%	\$\$
	22"x48"x7/8"	Class A	86454	0.80	35	0.90	White	C	Low		70%	\$\$
	24"x24"x7/8"	Class A	87200	0.80	35	0.90	White	C	Low		70%	\$\$
	24"x42"x7/8"	Class A	86456	0.80	35	0.90	White	C	Low		70%	\$\$
	24"x44"x7/8"	Class A	86457	0.80	35	0.90	White	C	Low		70%	\$\$
	24"x48"x7/8"	Class A	89600	0.80	35	0.90	White	C	Low		70%	\$\$
	24"x72"x7/8"	Class A	89660	0.80	35	0.90	White	C	Low		70%	\$\$
	27"x30"x7/8"	Class A	86458	0.80	35	0.90	White	C	Low		70%	\$\$
	27"x60"x7/8"	Class A	86460	0.80	35	0.90	White	C	Low		70%	\$\$
	28"x30"x7/8"	Class A	86459	0.80	35	0.90	White	C	Low		70%	\$\$
28"x60"x7/8"	Class A	86461	0.80	35	0.90	White	C	Low		70%	\$\$	
30"x30"x7/8"	Class A	86500	0.80	35	0.90	White	C	Low		70%	\$\$	
30"x54"x7/8"	Class A	86464	0.80	35	0.90	White	C	Low		70%	\$\$	
30"x56"x7/8"	Class A	86465	0.80	35	0.90	White	C	Low		70%	\$\$	
30"x60"x7/8"	Class A	86466	0.80	35	0.90	White	C	Low		70%	\$\$	
SLT	4"x48"x7/8"	Class A	86440	0.80	35	0.90	White	C	Low		70%	\$\$
	4"x60"x7/8"	Class A	86441	0.80	35	0.90	White	C	Low		70%	\$\$
	4"x72"x7/8"	Class A	86467	0.80	35	0.90	White	C	Low		70%	\$\$
	6"x48"x7/8"	Class A	86442	0.80	35	0.90	White	C	Low		70%	\$\$
	6"x60"x7/8"	Class A	86443	0.80	35	0.90	White	C	Low		70%	\$\$
	6"x72"x7/8"	Class A	86468	0.80	35	0.90	White	C	Low		70%	\$\$
	12"x48"x7/8"	Class A	86444	0.80	35	0.90	White	C	Low		70%	\$\$
	12"x60"x7/8"	Class A	86445	0.80	35	0.90	White	C	Low		70%	\$\$
12"x72"x7/8"	Class A	86446	0.80	35	0.90	White	C	Low		70%	\$\$	

Low Emissions (VOC)
Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.1 - 2010 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at productguide.ulenvironment.com.

ClimaPlus™ Warranty Performance³
Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content
Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

USG MARS™ HIGH-NRC
LOGIX™ FIELD PANELS
80/35

Plant-Based Binder

USG MARS™ HIGH-NRC
LOGIX™ CHANNEL PANELS
80/35

Plant-Based Binder

USG MARS™/MARS™ HIGH-NRC LOGIX™ ACOUSTICAL PANELS 80/35


CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER

ORDER SAMPLES/LITERATURE
USG: samplit@usg.com
fax: 888.874.2348 | usg.com
CGC: contact Sales Representative
TECHNICAL SERVICES
800.USG.4YOU (874-4968)

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
ULCOM/GG
UL2818



USG MARS™ HIGH-NRC LOGIX™ FIELD PANELS 80/35

Plant-Based Binder

USG MARS™ HIGH-NRC LOGIX™ CHANNEL PANELS 80/35

Plant-Based Binder

Edge	Panel Size ⁵	Fire Rating	Item No.	UL Classified		LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
				NRC	CAC Min.							
FLB	20"x54"x7/8"	Class A	86479	0.80	35	0.90	White	D, E, F	Low	70%	70%	\$\$
	20"x56"x7/8"	Class A	86480	0.80	35	0.90	White	D, E, F	Low	70%	70%	\$\$
	20"x60"x7/8"	Class A	86481	0.80	35	0.90	White	D, E, F	Low	70%	70%	\$\$
	21"x24"x7/8"	Class A	86483	0.80	35	0.90	White	D, E, F	Low	70%	70%	\$\$
	21"x48"x7/8"	Class A	86484	0.80	35	0.90	White	D, E, F	Low	70%	70%	\$\$
	22"x24"x7/8"	Class A	86485	0.80	35	0.90	White	D, E, F	Low	70%	70%	\$\$
	22"x48"x7/8"	Class A	86486	0.80	35	0.90	White	D, E, F	Low	70%	70%	\$\$
	24"x24"x7/8"	Class A	87100	0.80	35	0.90	White	D, E, F	Low	70%	70%	\$\$
	24"x42"x7/8"	Class A	86488	0.80	35	0.90	White	D, E, F	Low	70%	70%	\$\$
	24"x44"x7/8"	Class A	86489	0.80	35	0.90	White	D, E, F	Low	70%	70%	\$\$
	24"x48"x7/8"	Class A	89500	0.80	35	0.90	White	D, E, F	Low	70%	70%	\$\$
	24"x72"x7/8"	Class A	89670	0.80	35	0.90	White	D, E, F	Low	70%	70%	\$\$
	27"x30"x7/8"	Class A	86490	0.80	35	0.90	White	D, E, F	Low	70%	70%	\$\$
	27"x60"x7/8"	Class A	86491	0.80	35	0.90	White	D, E, F	Low	70%	70%	\$\$
	28"x30"x7/8"	Class A	86492	0.80	35	0.90	White	D, E, F	Low	70%	70%	\$\$
	28"x60"x7/8"	Class A	86493	0.80	35	0.90	White	D, E, F	Low	70%	70%	\$\$
	30"x30"x7/8"	Class A	86400	0.80	35	0.90	White	D, E, F	Low	70%	70%	\$\$
	30"x54"x7/8"	Class A	86501	0.80	35	0.90	White	D, E, F	Low	70%	70%	\$\$
	30"x56"x7/8"	Class A	86496	0.80	35	0.90	White	D, E, F	Low	70%	70%	\$\$
	30"x60"x7/8"	Class A	86497	0.80	35	0.90	White	D, E, F	Low	70%	70%	\$\$
FLB	4"x48"x7/8"	Class A	86475	0.80	35	0.90	White	D, E, F	Low	70%	70%	\$\$
	4"x60"x7/8"	Class A	86476	0.80	35	0.90	White	D, E, F	Low	70%	70%	\$\$
	4"x72"x7/8"	Class A	86473	0.80	35	0.90	White	D, E, F	Low	70%	70%	\$\$
	6"x48"x7/8"	Class A	86331	0.80	35	0.90	White	D, E, F	Low	70%	70%	\$\$
	6"x48"x7/8"	Class A	86333	0.80	35	0.90	White	D, E, F	Low	70%	70%	\$\$
	6"x72"x7/8"	Class A	86474	0.80	35	0.90	White	D, E, F	Low	70%	70%	\$\$
	12"x48"x7/8"	Class A	86505	0.80	35	0.90	White	D, E, F	Low	70%	70%	\$\$
	12"x60"x7/8"	Class A	86477	0.80	35	0.90	White	D, E, F	Low	70%	70%	\$\$
	12"x72"x7/8"	Class A	86478	0.80	35	0.90	White	D, E, F	Low	70%	70%	\$\$

Low Emissions (VOC)
Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.1 - 2010 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at productguide.ulenvironment.com.

ClimaPlus™ Warranty Performance³
Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content
Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

USG MARS™/MARS™ HIGH-NRC LOGIX™ ACOUSTICAL PANELS 85/35

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER

ORDER SAMPLES/LITERATURE
USG: samplitt@usg.com
fax: 888 874-2348 | usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com

TECHNICAL SERVICES
800 USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
ULCOM/GG
UL2818



30 YEAR LIMITED SYSTEM
WARRANTY
• No Visible Sag
• Mold/Mildew Protection



BALANCED
ACOUSTICS



HIGH
RECYCLED
CONTENT



Plant-Based
Binder



Edge	Panel Size ⁵	Fire Rating	Item No.	NRC	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
SQ <input type="checkbox"/>	20"x54"x7/8"	Class A	80100	0.85	35	0.90	White	A	Low		65%	\$\$
	20"x56"x7/8"	Class A	80101	0.85	35	0.90	White	A	Low		65%	\$\$
	20"x60"x7/8"	Class A	80102	0.85	35	0.90	White	A	Low		65%	\$\$
	21"x24"x7/8"	Class A	80103	0.85	35	0.90	White	A,B	Low		65%	\$\$
	21"x48"x7/8"	Class A	80104	0.85	35	0.90	White	A	Low		65%	\$\$
	22"x24"x7/8"	Class A	80105	0.85	35	0.90	White	A,B	Low		65%	\$\$
	22"x48"x7/8"	Class A	80106	0.85	35	0.90	White	A	Low		65%	\$\$
	24"x24"x7/8"	Class A	88134	0.85	35	0.90	White	A,B	Low		65%	\$\$
	24"x42"x7/8"	Class A	80107	0.85	35	0.90	White	A	Low		65%	\$\$
	24"x44"x7/8"	Class A	80108	0.85	35	0.90	White	A	Low		65%	\$\$
	24"x48"x7/8"	Class A	89134	0.85	35	0.90	White	A	Low		65%	\$\$
	24"x72"x7/8"	Class A	89663	0.85	35	0.90	White	A	Low		65%	\$\$
	27"x30"x7/8"	Class A	80109	0.85	35	0.90	White	A	Low		65%	\$\$
	27"x60"x7/8"	Class A	80110	0.85	35	0.90	White	A	Low		65%	\$\$
	28"x30"x7/8"	Class A	80111	0.85	35	0.90	White	A	Low		65%	\$\$
28"x60"x7/8"	Class A	80112	0.85	35	0.90	White	A	Low		65%	\$\$	
30"x30"x7/8"	Class A	80113	0.85	35	0.90	White	A	Low		65%	\$\$	
30"x54"x7/8"	Class A	80114	0.85	35	0.90	White	A	Low		65%	\$\$	
30"x56"x7/8"	Class A	80115	0.85	35	0.90	White	A	Low		65%	\$\$	
30"x60"x7/8"	Class A	89140	0.85	35	0.90	White	A	Low		65%	\$\$	
SQ <input type="checkbox"/>	4"x48"x7/8"	Class A	80116	0.85	35	0.90	White	A	Low		65%	\$\$
	4"x60"x7/8"	Class A	80117	0.85	35	0.90	White	A	Low		65%	\$\$
	4"x72"x7/8"	Class A	80118	0.85	35	0.90	White	A	Low		65%	\$\$
	6"x48"x7/8"	Class A	80119	0.85	35	0.90	White	A	Low		65%	\$\$
	6"x60"x7/8"	Class A	80120	0.85	35	0.90	White	A	Low		65%	\$\$
	6"x72"x7/8"	Class A	80121	0.85	35	0.90	White	A	Low		65%	—
	12"x12"x7/8"	Class A	80122	0.85	35	0.90	White	A	Low		65%	\$\$
	12"x24"x7/8"	Class A	86665	0.85	35	0.90	White	A	Low		65%	\$\$
	12"x48"x7/8"	Class A	80123	0.85	35	0.90	White	A	Low		65%	\$\$
	12"x60"x7/8"	Class A	80124	0.85	35	0.90	White	A	Low		65%	\$\$
12"x72"x7/8"	Class A	80125	0.85	35	0.90	White	A	Low		65%	\$\$	

Low Emissions (VOC)
Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.1 - 2010 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at productguide.ulenvironment.com.

ClimaPlus™ Warranty Performance³
Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content
Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

USG MARS™ HIGH-NRC
LOGIX™ FIELD PANELS
85/35

Plant-Based Binder

USG MARS™ HIGH-NRC
LOGIX™ CHANNEL PANELS
85/35

Plant-Based Binder

USG MARS™/MARS™ HIGH-NRC LOGIX™ ACOUSTICAL PANELS 85/35

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER

ORDER SAMPLES/LITERATURE
USG: samplit@usg.com
fax: 888.874.2348 | usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com

TECHNICAL SERVICES
800 USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
ULCOM/GG
UL2818



UL Classified

Edge	Panel Size ⁵	Fire Rating	Item No.	NRC	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
SLT	20"x54"x7/8"	Class A	80126	0.85	35	0.90	White	C	Low		65%	\$\$
	20"x56"x7/8"	Class A	80127	0.85	35	0.90	White	C	Low		65%	\$\$
	20"x60"x7/8"	Class A	80128	0.85	35	0.90	White	C	Low		65%	\$\$
	21"x24"x7/8"	Class A	80129	0.85	35	0.90	White	C	Low		65%	\$\$
	21"x48"x7/8"	Class A	80130	0.85	35	0.90	White	C	Low		65%	\$\$
	22"x24"x7/8"	Class A	80131	0.85	35	0.90	White	C	Low		65%	\$\$
	22"x48"x7/8"	Class A	80132	0.85	35	0.90	White	C	Low		65%	\$\$
	24"x24"x7/8"	Class A	88135	0.85	35	0.90	White	C	Low		65%	\$\$
	24"x42"x7/8"	Class A	80133	0.85	35	0.90	White	C	Low		65%	\$\$
	24"x44"x7/8"	Class A	80134	0.85	35	0.90	White	C	Low		65%	\$\$
	24"x48"x7/8"	Class A	89135	0.85	35	0.90	White	C	Low		65%	\$\$
	24"x72"x7/8"	Class A	89665	0.85	35	0.90	White	C	Low		65%	\$\$
	27"x30"x7/8"	Class A	80135	0.85	35	0.90	White	C	Low		65%	\$\$
	27"x60"x7/8"	Class A	80136	0.85	35	0.90	White	C	Low		65%	\$\$
	28"x30"x7/8"	Class A	80137	0.85	35	0.90	White	C	Low		65%	\$\$
28"x60"x7/8"	Class A	80138	0.85	35	0.90	White	C	Low		65%	\$\$	
30"x30"x7/8"	Class A	80139	0.85	35	0.90	White	C	Low		65%	\$\$	
30"x54"x7/8"	Class A	80140	0.85	35	0.90	White	C	Low		65%	\$\$	
30"x56"x7/8"	Class A	80141	0.85	35	0.90	White	C	Low		65%	\$\$	
30"x60"x7/8"	Class A	89141	0.85	35	0.90	White	C	Low		65%	\$\$	
SLT	4"x48"x7/8"	Class A	80142	0.85	35	0.90	White	C	Low		65%	\$\$
	4"x60"x7/8"	Class A	80143	0.85	35	0.90	White	C	Low		65%	\$\$
	4"x72"x7/8"	Class A	80144	0.85	35	0.90	White	C	Low		65%	\$\$
	6"x48"x7/8"	Class A	80145	0.85	35	0.90	White	C	Low		65%	\$\$
	6"x60"x7/8"	Class A	80146	0.85	35	0.90	White	C	Low		65%	\$\$
	6"x72"x7/8"	Class A	80147	0.85	35	0.90	White	C	Low		65%	\$\$
	12"x12"x7/8"	Class A	80148	0.85	35	0.90	White	C	Low		65%	\$\$
	12"x24"x7/8"	Class A	86664	0.85	35	0.90	White	C	Low		65%	\$\$
	12"x48"x7/8"	Class A	80149	0.85	35	0.90	White	C	Low		65%	\$\$
	12"x60"x7/8"	Class A	80150	0.85	35	0.90	White	C	Low		65%	\$\$
	12"x72"x7/8"	Class A	80151	0.85	35	0.90	White	C	Low		65%	\$\$

Low Emissions (VOC)
Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.1 - 2010 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at productguide.ulenvironment.com.

ClimaPlus™ Warranty Performance³
Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content
Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

USG MARS™ HIGH-NRC
LOGIX™ FIELD PANELS
85/35
Plant-Based Binder

USG MARS™ HIGH-NRC
LOGIX™ CHANNEL PANELS
85/35
Plant-Based Binder

USG MARS™/MARS™ HIGH-NRC LOGIX™ ACOUSTICAL PANELS 85/35

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER


ORDER SAMPLES/LITERATURE
USG: samplitt@usg.com
fax: 888 874-2348 | usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com

TECHNICAL SERVICES
800 USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
ULCOM/GG
UL2818



UL Classified

Edge	Panel Size ⁵	Fire Rating	Item No.	NRC	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
FLB	20"x54"x7/8"	Class A	80152	0.85	35	0.90	White	D,E,F	Low		65%	\$\$
	20"x56"x7/8"	Class A	80153	0.85	35	0.90	White	D,E,F	Low		65%	\$\$
	20"x60"x7/8"	Class A	80154	0.85	35	0.90	White	D,E,F	Low		65%	\$\$
	21"x24"x7/8"	Class A	80155	0.85	35	0.90	White	D,E,F	Low		65%	\$\$
	21"x48"x7/8"	Class A	80156	0.85	35	0.90	White	D,E,F	Low		65%	\$\$
	22"x24"x7/8"	Class A	80157	0.85	35	0.90	White	D,E,F	Low		65%	\$\$
	22"x48"x7/8"	Class A	80158	0.85	35	0.90	White	D,E,F	Low		65%	\$\$
	24"x24"x7/8"	Class A	88136	0.85	35	0.90	White	D,E,F	Low		65%	\$\$
	24"x42"x7/8"	Class A	80159	0.85	35	0.90	White	D,E,F	Low		65%	\$\$
	24"x44"x7/8"	Class A	80160	0.85	35	0.90	White	D,E,F	Low		65%	\$\$
	24"x48"x7/8"	Class A	89136	0.85	35	0.90	White	D,E,F	Low		65%	\$\$
	24"x72"x7/8"	Class A	89668	0.85	35	0.90	White	D,E,F	Low		65%	\$\$
	27"x30"x7/8"	Class A	80161	0.85	35	0.90	White	D,E,F	Low		65%	\$\$
	27"x60"x7/8"	Class A	80162	0.85	35	0.90	White	D,E,F	Low		65%	\$\$
	28"x30"x7/8"	Class A	80163	0.85	35	0.90	White	D,E,F	Low		65%	\$\$
	28"x60"x7/8"	Class A	80164	0.85	35	0.90	White	D,E,F	Low		65%	\$\$
	30"x30"x7/8"	Class A	80165	0.85	35	0.90	White	D,E,F	Low		65%	\$\$
	30"x54"x7/8"	Class A	80166	0.85	35	0.90	White	D,E,F	Low		65%	\$\$
	30"x56"x7/8"	Class A	80167	0.85	35	0.90	White	D,E,F	Low		65%	\$\$
	30"x60"x7/8"	Class A	89142	0.85	35	0.90	White	D,E,F	Low		65%	\$\$
FLB	4"x48"x7/8"	Class A	80168	0.85	35	0.90	White	D,E,F	Low		65%	\$\$
	4"x60"x7/8"	Class A	80169	0.85	35	0.90	White	D,E,F	Low		65%	\$\$
	4"x72"x7/8"	Class A	80170	0.85	35	0.90	White	D,E,F	Low		65%	\$\$
	6"x48"x7/8"	Class A	80171	0.85	35	0.90	White	D,E,F	Low		65%	\$\$
	6"x60"x7/8"	Class A	80172	0.85	35	0.90	White	D,E,F	Low		65%	\$\$
	6"x72"x7/8"	Class A	80173	0.85	35	0.90	White	D,E,F	Low		65%	\$\$
	12"x12"x7/8"	Class A	80174	0.85	35	0.90	White	D,E,F	Low		65%	\$\$
	12"x24"x7/8"	Class A	86663	0.85	35	0.90	White	D,E,F	Low		65%	\$\$
	12"x48"x7/8"	Class A	80175	0.85	35	0.90	White	D,E,F	Low		65%	\$\$
	12"x60"x7/8"	Class A	80176	0.85	35	0.90	White	D,E,F	Low		65%	\$\$
	12"x72"x7/8"	Class A	80177	0.85	35	0.90	White	D,E,F	Low		65%	\$\$

Low Emissions (VOC)
Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.1 - 2010 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at productguide.ulenvironment.com.

ClimaPlus™ Warranty Performance³
Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content
Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

USG MARS™ HIGH-NRC
LOGIX™ FIELD PANELS
85/35

Plant-Based Binder

USG MARS™ HIGH-NRC
LOGIX™ CHANNEL PANELS
85/35

Plant-Based Binder

USG MARS™/MARS™ HIGH-NRC LOGIX™ ACOUSTICAL PANELS 90/30

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER

ORDER SAMPLES/LITERATURE
USG: samplit@usg.com
fax: 888.874.2348 | usg.com
CGC: contact Sales Representative
usgdesignstudio.com
cgcdesignstudio.com

TECHNICAL SERVICES
800 USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
ULCOM/CG
UL2818



UL Classified

Edge	Panel Size ⁵	Fire Rating	Item No.	NRC	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
SQ <input type="checkbox"/>	20"x54"x1"	Class A	80200	0.90	30	0.90	White	A	Low		66%	\$\$
	20"x56"x1"	Class A	80201	0.90	30	0.90	White	A	Low		66%	\$\$
	20"x60"x1"	Class A	80202	0.90	30	0.90	White	A	Low		66%	\$\$
	21"x24"x1"	Class A	80203	0.90	30	0.90	White	A,B	Low		66%	\$\$
	21"x48"x1"	Class A	80204	0.90	30	0.90	White	A	Low		66%	\$\$
	22"x24"x1"	Class A	80205	0.90	30	0.90	White	A,B	Low		66%	\$\$
	22"x48"x1"	Class A	80206	0.90	30	0.90	White	A	Low		66%	\$\$
	24"x24"x1"	Class A	88137	0.90	30	0.90	White	A,B	Low		66%	\$\$
	24"x42"x1"	Class A	80207	0.90	30	0.90	White	A	Low		66%	\$\$
	24"x44"x1"	Class A	80208	0.90	30	0.90	White	A	Low		66%	\$\$
	24"x48"x1"	Class A	89137	0.90	30	0.90	White	A	Low		66%	\$\$
	24"x72"x1"	Class A	89674	0.90	30	0.90	White	A	Low		66%	\$\$
	27"x30"x1"	Class A	80209	0.90	30	0.90	White	A	Low		66%	\$\$
	27"x60"x1"	Class A	80210	0.90	30	0.90	White	A	Low		66%	\$\$
	28"x30"x1"	Class A	80211	0.90	30	0.90	White	A	Low		66%	\$\$
	28"x60"x1"	Class A	80212	0.90	30	0.90	White	A	Low		66%	\$\$
	30"x30"x1"	Class A	80213	0.90	30	0.90	White	A	Low		66%	\$\$
	30"x54"x1"	Class A	80214	0.90	30	0.90	White	A	Low		66%	\$\$
	30"x56"x1"	Class A	80215	0.90	30	0.90	White	A	Low		66%	\$\$
	30"x60"x1"	Class A	89143	0.90	30	0.90	White	A	Low		66%	\$\$
SQ <input type="checkbox"/>	4"x48"x1"	Class A	80216	0.90	30	0.90	White	A	Low		66%	\$\$
	4"x60"x1"	Class A	80217	0.90	30	0.90	White	A	Low		66%	\$\$
	4"x72"x1"	Class A	80218	0.90	30	0.90	White	A	Low		66%	\$\$
	6"x48"x1"	Class A	80219	0.90	30	0.90	White	A	Low		66%	\$\$
	6"x60"x1"	Class A	80220	0.90	30	0.90	White	A	Low		66%	\$\$
	6"x72"x1"	Class A	80221	0.90	30	0.90	White	A	Low		66%	\$\$
	12"x12"x1"	Class A	80222	0.90	30	0.90	White	A	Low		66%	\$\$
	12"x24"x1"	Class A	86137	0.90	30	0.90	White	A	Low		66%	\$\$
	12"x48"x1"	Class A	80223	0.90	30	0.90	White	A	Low		66%	\$\$
	12"x60"x1"	Class A	80224	0.90	30	0.90	White	A	Low		66%	\$\$
12"x72"x1"	Class A	80225	0.90	30	0.90	White	A	Low		66%	\$\$	

Low Emissions (VOC)
Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.1 - 2010 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at productguide.ulenvironment.com.

ClimaPlus™ Warranty Performance³
Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content
Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

USG MARS™ HIGH-NRC
LOGIX™ FIELD PANELS
90/30
Plant-Based Binder

USG MARS™ HIGH-NRC
LOGIX™ CHANNEL PANELS
90/30
Plant-Based Binder

USG MARS™/MARS™ HIGH-NRC LOGIX™ ACOUSTICAL PANELS 90/30

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER

ORDER SAMPLES/LITERATURE
USG: samplitt@usg.com
fax: 888 874-2348 | usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com

TECHNICAL SERVICES
800 USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
ULCOM/GG
UL2818



YEAR LIMITED SYSTEM
WARRANTY
• No Visible Sag
• Mold/Mildew Protection



BALANCED
ACOUSTICS



HIGH
RECYCLED
CONTENT



Plant-Based
Binder



Edge	Panel Size ⁵	Fire Rating	Item No.	NRC	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
SLT	20"x54"x1"	Class A	80226	0.90	30	0.90	White	C	Low		66%	\$\$
	20"x56"x1"	Class A	80227	0.90	30	0.90	White	C	Low		66%	\$\$
	20"x60"x1"	Class A	80228	0.90	30	0.90	White	C	Low		66%	\$\$
	21"x24"x1"	Class A	80229	0.90	30	0.90	White	C	Low		66%	\$\$
	21"x48"x1"	Class A	80230	0.90	30	0.90	White	C	Low		66%	\$\$
	22"x24"x1"	Class A	80231	0.90	30	0.90	White	C	Low		66%	\$\$
	22"x48"x1"	Class A	80232	0.90	30	0.90	White	C	Low		66%	\$\$
	24"x24"x1"	Class A	88138	0.90	30	0.90	White	C	Low		66%	\$\$
	24"x42"x1"	Class A	80233	0.90	30	0.90	White	C	Low		66%	\$\$
	24"x44"x1"	Class A	80234	0.90	30	0.90	White	C	Low		66%	\$\$
	24"x48"x1"	Class A	89138	0.90	30	0.90	White	C	Low		66%	\$\$
	24"x72"x1"	Class A	89675	0.90	30	0.90	White	C	Low		66%	\$\$
	27"x30"x1"	Class A	80235	0.90	30	0.90	White	C	Low		66%	\$\$
	27"x60"x1"	Class A	80236	0.90	30	0.90	White	C	Low		66%	\$\$
	28"x30"x1"	Class A	80237	0.90	30	0.90	White	C	Low		66%	\$\$
28"x60"x1"	Class A	80238	0.90	30	0.90	White	C	Low		66%	\$\$	
30"x30"x1"	Class A	80239	0.90	30	0.90	White	C	Low		66%	\$\$	
30"x54"x1"	Class A	80240	0.90	30	0.90	White	C	Low		66%	\$\$	
30"x56"x1"	Class A	80241	0.90	30	0.90	White	C	Low		66%	\$\$	
30"x60"x1"	Class A	89144	0.90	30	0.90	White	C	Low		66%	\$\$	
SLT	4"x48"x1"	Class A	80242	0.90	30	0.90	White	C	Low		66%	\$\$
	4"x60"x1"	Class A	80243	0.90	30	0.90	White	C	Low		66%	\$\$
	4"x72"x1"	Class A	80244	0.90	30	0.90	White	C	Low		66%	\$\$
	6"x48"x1"	Class A	80245	0.90	30	0.90	White	C	Low		66%	\$\$
	6"x60"x1"	Class A	80246	0.90	30	0.90	White	C	Low		66%	\$\$
	6"x72"x1"	Class A	80247	0.90	30	0.90	White	C	Low		66%	\$\$
	12"x12"x1"	Class A	80248	0.90	30	0.90	White	C	Low		66%	\$\$
	12"x24"x1"	Class A	86138	0.90	30	0.90	White	C	Low		66%	\$\$
	12"x48"x1"	Class A	80249	0.90	30	0.90	White	C	Low		66%	\$\$
	12"x60"x1"	Class A	80250	0.90	30	0.90	White	C	Low		66%	\$\$
	12"x72"x1"	Class A	80251	0.90	30	0.90	White	C	Low		66%	\$\$

Low Emissions (VOC)
Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.1 - 2010 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at productguide.ulenvironment.com.

ClimaPlus™ Warranty Performance³
Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content
Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

USG MARS™ HIGH-NRC LOGIX™ FIELD PANELS 90/30

Plant-Based Binder

USG MARS™ HIGH-NRC LOGIX™ CHANNEL PANELS 90/30

Plant-Based Binder

USG MARS™/MARS™ HIGH-NRC LOGIX™ ACOUSTICAL PANELS 90/30


CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER

ORDER SAMPLES/LITERATURE
USG: samplit@usg.com
fax: 888.874.2348 | usg.com
CGC: contact Sales Representative
usgdesignstudio.com
cgcdesignstudio.com

TECHNICAL SERVICES
800 USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
ULCOM/CG
UL2818



USG MARS™ HIGH-NRC LOGIX™ FIELD PANELS 90/30

Plant-Based Binder

USG MARS™ HIGH-NRC LOGIX™ CHANNEL PANELS 90/30

Plant-Based Binder

Edge	Panel Size ⁵	Fire Rating	Item No.	UL Classified		LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
				NRC	CAC Min.							
FLB	20"x54"x1"	Class A	80252	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$
	20"x56"x1"	Class A	80253	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$
	20"x60"x1"	Class A	80254	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$
	21"x24"x1"	Class A	80255	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$
	21"x48"x1"	Class A	80256	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$
	22"x24"x1"	Class A	80257	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$
	22"x48"x1"	Class A	80258	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$
	24"x24"x1"	Class A	88139	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$
	24"x42"x1"	Class A	80259	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$
	24"x44"x1"	Class A	80260	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$
	24"x48"x1"	Class A	89139	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$
	24"x72"x1"	Class A	89678	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$
	27"x30"x1"	Class A	80261	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$
	27"x60"x1"	Class A	80262	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$
	28"x30"x1"	Class A	80263	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$
	28"x60"x1"	Class A	80264	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$
	30"x30"x1"	Class A	80265	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$
	30"x54"x1"	Class A	80266	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$
	30"x56"x1"	Class A	80267	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$
	30"x60"x1"	Class A	89145	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$
FLB	4"x48"x1"	Class A	80268	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$
	4"x60"x1"	Class A	80269	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$
	4"x72"x1"	Class A	80270	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$
	6"x48"x1"	Class A	80271	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$
	6"x60"x1"	Class A	80272	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$
	6"x72"x1"	Class A	80273	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$
	12"x12"x1"	Class A	80274	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$
	12"x24"x1"	Class A	86139	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$
	12"x48"x1"	Class A	80275	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$
	12"x60"x1"	Class A	80276	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$
	12"x72"x1"	Class A	80277	0.90	30	0.90	White	D,E,F	Low	Green	66%	\$\$

Low Emissions (VOC)
Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v.1.1 - 2010 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at productguide.ulenvironment.com.

ClimaPlus™ Warranty Performance³
Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content
Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

USG MARS™/MARS™ HIGH-NRC LOGIX™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER

ORDER SAMPLES/LITERATURE
USG: samplitt@usg.com
fax: 888 874-2348 | usg.com
CGC: contact Sales Representative

**FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL**
usgdesignstudio.com
cgcdesignstudio.com

TECHNICAL SERVICES
800 USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
ULCOM/GG
UL2818

GRID PROFILE OPTIONS

PHYSICAL DATA/ FOOTNOTES



A USG DX [®] /DXL [™]	B ⁴ USG Centricitee [™] DXT [™]	C USG DX [®] /DXL [™]	D USG Centricitee [™] DXT [™]	E USG Fineline [®] DXF [™]	F USG Identitee [®] DXI [™]

Product literature
Data sheet: IS274
System guide: IS268

ASTM E1264 classification
Type IV, Form 1 and 2, Pattern E, G

**ASTM E84 and CAN/ULC S102
surface-burning characteristics**
Class A
Flame spread: 25 or less
Smoke developed: 50 or less

Weight
1.03 lb./sq. ft. (3/4")
1.05-1.12 lb./sq. ft. (7/8")
1.26 lb./sq. ft. (1")

Online tools
usgdesignstudio.com or cgcdesignstudio.com

Thermal resistance
R-2.2 (3/4")

Maintenance
Can be cleaned easily with a soft brush or vacuum. To clean panel, use a clean white cloth with water or a mild detergent and wipe surface.

Maximum backloading
See *USG 30-Year Limited System Warranty Commercial Applications (SC2102)*.

- Notes**
- For details see LEED report tool at usgdesignstudio.com or cgcdesignstudio.com.
 - LR values are shown as averages.
 - Panel face and back surfaces treated with a proprietary broad-spectrum antimicrobial standard formulation that inhibits and retards the growth of mold and mildew. For details, see *USG 30-Year Limited System Warranty Commercial Applications (SC2102)* and *USG ClimaPlus™ Ceilings Certification of Performance (SC2451)*.
 - Maximum 2'x2' with SQ edge panels.
 - Stabilizer bar required if opening ≥ 60".

Notice

The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

IS274/rev. 3-17
© 2017 USG Corporation and/or its affiliates. All rights reserved. Printed in U.S.A.

Manufactured by
USG Interiors, LLC
550 West Adams Street
Chicago, IL 60661

The trademarks USG, CGC, CENTRICITEE, CLIMAPLUS, DONN, DX, DXF, DXI, DXL, DXT, FINELINE, HALCYON, IDENTITEE, LOGIX, MARS, IT'S YOUR WORLD. BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

