


## SUBMITTAL SHEET

## Product(s): Niche Bead Style 641



**Advantages:** Qualifies for LEED® points. Made from rust proof, dent resistant PVC to reduce job site and handling damage.

**Applicable Standards:** Rigid PVC products made by Trim-Tex meet ASTM specifications D3678-97, D1784-03, C1047-99 and achieve a Class A rating for flame spread and smoke developed when tested under ASTM E84-10.

**Surface Characteristics:** Trim-Tex products are made from PVC. PVC does not support combustion and is self extinguishing when the source of flame or heat is removed.

**Installation:** Set back the drywall 5%". Snip the bead to length and dry fit. Install with Trim-Tex 847 Spray Adhesive and ½" divergent staples. Place a bead of adhesive caulk at the seam and wipe away the excess. Detailed installation instructions are included with each product.

**Finishing:** To improve the bondability of drywall compounds, textures, & plaster products to any bead, use MUD-MAX Drywall Compound Additive. Priming is not required. Always use a high quality paint. North Safety Products are distributed by Trim-Tex.

Job Name\_

|--|

Available Sizes & Lengths			
Stock #	Length	Pcs/Box	
64110	10'	15	

Contractor	Date
Approvals (Signatures o	r Stamps)
Tipprorate (eignature)	