

# CGC OLYMPIA MICRO™

## CLIMAPLUS™ PERFORMANCE

CGC Olympia Micro Panels/  
CGC Donn Finline DXF  
Suspension System

Flat White  
050

### FEATURES AND BENEFITS

- Non-directional pattern reduces installation time and waste.
- Economical, fine-textured panel.
- Excellent light reflective finish (LR .86) reduces light fixtures and energy use.
- Available in Optimized Recycled Content formulations to help maximize LEED recycled content contribution.
- USDA Certified Biobased Product<sup>7</sup>.
- Available with .60 NRC.
- ClimaPlus™ 30-year lifetime system warranty against visible sag, mould and mildew.

### APPLICATIONS

- Offices
- Classrooms
- Reception/Lobby areas
- Hotels
- Conference areas
- Retail stores

### SUBSTRATE

- Wet-formed mineral fiber

FINE-TEXTURED PANEL

# CGC OLYMPIA MICRO™

## CLIMAPLUS™ PERFORMANCE

**CUSTOMER SERVICE**  
 Ontario/Atlantic Canada : 800.387.2690  
 Quebec/Eastern Ontario : 800.361.1310  
 Western Canada : 800.242.4418

**COMPANY WEBSITE**  
 cgcinc.com

**SEE LEED REPORT TOOL**  
 for detailed sustainability  
 information, as well as the  
**MOST UP-TO-DATE**  
**TECHNICAL INFORMATION,**  
 all available at  
 cgcdesignstudio.com

**30 YEAR SYSTEM WARRANTY**  
 • No Visible Sag  
 • Mould/Mildew Protection

**10 YEAR AVAILABILITY**  
 4211, 4221, 4231,  
 4411, 4421, 4742,  
 4744

**HRC HIGH RECYCLED CONTENT**



### UL Classified

Edge	Panel Size	Class	Item No.	NRC <sup>5</sup>	CAC Min.	LR <sup>2</sup>	Colour	Grid Options	VOC Emissions	Anti-Mould & Mildew	Recycled Content <sup>1</sup>	Panel Cost
SQ	2' x 2' x 5/8"	Class A	4210	—	35	.86	White	A, B, C	Low		43.7%	\$\$
	2' x 2' x 5/8"	Class A	4913	—	35	.86	White	A, B	Low		43.7%	\$\$
SQ	2' x 2' x 5/8"	Class A	4211	.50	30	.86	White	A, B, C	Low		43.7%	\$\$
	2' x 4' x 5/8"	Class A	4411	.50	30	.86	White	A, B	Low		43.7%	\$\$
	2' x 4' x 5/8"	Class A	4411HRC	.50	30	.86	White	A, B	Low		53.2% HRC	\$\$
	20" x 60" x 5/8"	Class A	4746	.50	30	.87	White	A, B	Low		43.7%	\$\$
	2' x 5' x 5/8"	Class A	4775	.50	30	.87	White	A, B	Low		43.7%	\$\$
SLT	2' x 2' x 5/8"	Class A	4221	.50	35	.86	White	D	Low		43.7%	\$\$
	2' x 2' x 5/8"	Class A	4221HRC	.50	35	.86	White	D	Low		53.2% HRC	\$\$
	2' x 4' x 5/8"	Class A	4421	.50	35	.86	White	D	Low		43.7%	\$\$
	2' x 4' x 5/8"	Class A	4421HRC	.50	35	.86	White	D	Low		53.2% HRC	\$\$
FLB	2' x 2' x 5/8"	Class A	4231	.50	35	.86	White	E, F, G, H	Low		43.7%	\$\$
	2' x 2' x 5/8"	Class A	4231HRC	.50	35	.86	White	E, F, G, H	Low		53.2% HRC	\$\$
	2' x 4' x 5/8"	Class A	4431	.50	35	.86	White	E, F, G, H	Low		43.7%	\$\$
SQ	2' x 2' x 3/4"	Class A	4750	.60	33	.86	White	A, B, C	Low		59.7% HRC	\$\$
	2' x 4' x 3/4"	Class A	4751	.60	33	.86	White	A, B	Low		59.7% HRC	\$\$
SLT	2' x 2' x 3/4"	Class A	4752	.60	35	.86	White	D	Low		59.7% HRC	\$\$
	2' x 4' x 3/4"	Class A	4753	.60	35	.86	White	D	Low		59.7% HRC	\$\$
FLB	2' x 2' x 3/4"	Class A	4754	.60	35	.86	White	E, F, G, H	Low		59.7% HRC	\$\$
	2' x 4' x 3/4"	Class A	4755	.60	35	.86	White	E, F, G, H	Low		59.7% HRC	\$\$
SLT <sup>3</sup>	2' x 4' x 3/4"	Class A	4742	.60	35	.86	White	D	Low		59.7% HRC	\$\$
ILT <sup>4</sup>	2' x 4' x 3/4"	Class A	4744	.60	35	.86	White	I, J	Low		59.7% HRC	\$\$

**CGC OLYMPIA MICRO UNPERFORATED**

**CGC OLYMPIA MICRO PANELS .50 NRC**

**CGC OLYMPIA MICRO PANELS .60 NRC**

**CGC OLYMPIA MICRO ILLUSION TWO/24 PANELS**

### PATTERN

**ILLUSION TWO/24** The look of 2' x 2' panels



### LEGEND

**Low Emissions (VOC)**

Low-emitting performance meets CA Specification 01350 (CA Dept. of Health Services Standard Practice for the testing of VOC emissions) and is listed on the CHPS database for low-emitting materials. USG Certificate of Compliance for Low VOC Emissions also available on usg.com.

**ClimaPlus™ Warranty Performance<sup>6</sup>**

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mould and mildew. Includes sag resistance performance.

**High Recycled Content**

Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per U.S. FTC guidelines.

**≥ .85 LR**

### GRID PROFILE OPTIONS

A DX*/DXL™	B DXW™	C' CENTRICITEE™ DXT™	D DX/DXL	E CENTRICITEE DXT	F IDENTITEE™ DXI™	G FINELINE* DXF™	H FINELINE 1/8 DXFF™	I CENTRICITEE DXT	J IDENTITEE DXI

### PHYSICAL DATA/NOTES

**Product literature**  
 Data sheet: SC2180E

**ASTM E1264 classification**  
 Type III, Form 2, Pattern CE

**ASTM E84 and CAN/ULC S102 surface burning characteristics**  
 Class A  
 Flame spread: 25  
 Smoke developed: 50  
**Weight**  
 0.78-1.03 lbs./sq. ft.

**Thermal resistance**  
 R-1.4 (5/8" panels)  
 R-1.7 (3/4" panels)  
**Maximum backloading**  
 See Warranty for details.  
**Maintenance**  
 Can be cleaned easily with a soft brush or vacuum.

**Notes**  
 1. For details, see LEED report tool at cgcdesignstudio.com.  
 2. LR values are shown as averages.  
 3. Panels have 15/16" routing.  
 4. Panels have 9/16" routing.

5. Mixing .50 and .60 NRC panels in the same ceiling plane is not recommended.  
 6. For details, see Ceiling Systems Limited Warranty Commercial Applications (CSC2102) and ClimaPlus Ceilings Certification of Performance (SC2451).

7. This product has achieved both BioPreferred initiatives: Federal Procurement Preference and Certified Product Labeling. See the complete listing of all USG ceiling panels on biopreferred.gov website.

