

PEBBLE™

Square Lay-in
medium texture



This economical, medium-textured panel provides excellent sound absorption options.

KEY SELECTION ATTRIBUTES

- Excellent sound absorption (perforated items)
- Easy-to-clean, durable surface
- Economical solution
- 30-Year Limited System Warranty against visible sag, mold, and mildew

TYPICAL APPLICATIONS

- Discount/grocery stores
- Locker rooms
- Utility rooms
- Lavatories/restrooms

COLOR



White
(WH)

DETAILS



1. Pebble™
2. Pebble with Prelude® 15/16" suspension system

PEBBLE™

Square Lay-in medium texture

UP TO **71%** RECYCLED CONTENT

Calculate LEED contribution at armstrongceilings.com/greengenie

LEED®

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/extended producer resp.
- bio-based materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

LOCATION DEPENDENT

VISUAL SELECTION

Edge Profile	Susp. Dwg. Pgs. 407-411 armstrongceilings.com/catdwgs	Item No.	Dimensions (Inches)
PEBBLE™ (Perforated)			
15/16" Square Lay-in	1	2983	24 x 48 x 5/8"
	1	2970	24 x 60 x 5/8"
	1	Other Size Panels	W: 12" – 30" / L: 12" – 60" 5/8" Thick
PEBBLE High NRC (Perforated)			
15/16" Square Lay-in	1	2988	24 x 24 x 1"
	1	2989	24 x 48 x 1"
	1	Other Size Panels	W: 12" – 30" / L: 12" – 60" 1" Thick
PEBBLE (Unperforated)			
15/16" Square Lay-in	1	2968	24 x 48 x 5/8"
	1	Other Size Panels	W: 12" – 30" / L: 12" – 60" 5/8" Thick


PERFORMANCE SELECTION

Dots represent high level of performance.

UL Classified Acoustics		NRC	+ CAC	=	Total Acoustics ¹	Fire Performance	Light Reflect	Anti-Mold & Mildew	Sag Resist	Certified Low VOC Emissions	Water Repel	Wash	Scrub	Impact	Soil	Recycled Content	Recycle Program	30-Yr Warranty
UL	NRC																	
0.70	N/A	•			–	Class A	0.89	•	•	–	–	•	•	•	•	•	–	•
0.70	N/A	•			–	Class A	0.89	•	•	–	–	•	•	•	•	•	–	•
N/A	N/A				–	N/A	0.89	•	•	–	–	•	•	•	•	•	–	•
0.80	N/A	•			–	Class A	0.89	•	•	–	–	•	•	•	•	•	–	•
0.80	N/A	•			–	Class A	0.89	•	•	–	–	•	•	•	•	•	–	•
N/A	N/A				–	N/A	0.89	•	•	–	–	•	•	•	•	•	–	•
0.50	N/A	•			–	Class A	0.89	•	•	–	•	•	•	•	•	•	–	•
N/A	N/A				–	N/A	0.89	•	•	–	•	•	•	•	•	•	–	•

¹Total Acoustics® ceiling panels have an ideal combination of noise reduction and sound-blocking performance in one product.

SUSPENSION SYSTEMS



PHYSICAL DATA

Material
Fiberglass with vinyl facing

Surface Finish
Scrubable vinyl film facing (UV protected)

Fire Performance
ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less (UL labeled).

ASTM E1264 Classification
Type XII, Form 1, Pattern E C
Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Mold/Mildew Protection
Ceiling panels with BioBlock® performance resist the growth of mold and mildew.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Acoustical Details
A CAC value of 37 can be achieved by backloading fiberglass products with Item 769 or 770.

Insulation Value
2968, 2970, 2983 - R Factor - 2.6 (BTU units)
R Factor - 0.46 (Watts units)
2988, 2989 - R Factor - 4.0 (BTU units)
R Factor - 0.70 (Watts units)

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com

Weight; Square Feet/Carton
2968, 2983 – 0.20 lbs/SF; 128 SF/ctn
2970 – 0.20 lbs/SF; 120 SF/ctn
2988, 2989 – 0.31 lbs/SF; 80 SF/ctn

Minimum Order Quantity
1 carton, excludes other size panels.

Metric Items Available
2983M, 2970M, 2988M, 2989M, 2968M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.