

# CGC RADAR™ ILLUSION™

CLIMAPLUS™ PERFORMANCE



CGC Radar Illusion Four/48 Panels/  
CGC Donn DX/DXL Suspension System

#### STANDARD COLOURS



Flat White  
050



Parchment  
103



Manila  
246



Straw  
143



Sandstone  
090



Taupe  
107

#### FEATURES AND BENEFITS

- Non-directional pattern offers fast, efficient installation.
- Face scores create illusion of a smaller scaled ceiling system.
- ClimaPlus™ 30-year lifetime system warranty against visible sag, mould and mildew.
- Optional Firecode® product designed to meet life-safety codes.


#### APPLICATIONS

- Schools
- Corridors
- General offices
- Retail stores

#### SUBSTRATE

- Wet-formed mineral fiber

LIGHTLY-TEXTURED PANEL





**UL Classified**

| Edge                                  | Panel Size           | Class <sup>2</sup> | Item No.    | NRC | CAC Min. | LR <sup>3</sup> | Colour <sup>4</sup>         | Grid Options | VOC Emissions | Anti-Mould & Mildew | Recycled Content <sup>1</sup> | Panel Cost |
|---------------------------------------|----------------------|--------------------|-------------|-----|----------|-----------------|-----------------------------|--------------|---------------|---------------------|-------------------------------|------------|
| CGCRADAR ILLUSION TWO/24 PANELS       | SLT <sup>5</sup><br> | Class A            | <b>2842</b> | .55 | 35       | .84             | White Standard <sup>8</sup> | A            | Low           |                     | 30.4-45.9%                    | \$\$       |
|                                       | ILT <sup>6</sup><br> |                    | <b>2844</b> | .55 | 35       | .84             | White                       | B, C         | Low           |                     | 45.9%                         | \$\$       |
| CGCRADAR ILLUSION FOUR/48 PANELS      | SLT <sup>5</sup><br> | Class A            | <b>2882</b> | .50 | 35       | .84             | White                       | A            | Low           |                     | 45.9%                         | \$\$       |
|                                       | ILT <sup>6</sup><br> |                    | <b>2884</b> | .50 | 35       | .84             | White                       | B, C         | Low           |                     | 45.9%                         | \$\$       |
| CGCRADAR ILLUSION EIGHT/12 PANELS     | SLT <sup>5</sup><br> | Class A            | <b>2852</b> | .55 | 35       | .84             | White                       | A            | Low           |                     | 45.9%                         | \$\$       |
|                                       | ILT <sup>6</sup><br> |                    | <b>2854</b> | .55 | 35       | .84             | White                       | B, C         | Low           |                     | 45.9%                         | \$\$       |
| CGCRADAR ILLUSION THIRTY-TWO/6 PANELS | SLT <sup>5</sup><br> | Class A            | <b>2862</b> | .50 | 35       | .84             | White                       | A            | Low           |                     | 45.9%                         | \$\$       |
|                                       | ILT <sup>6</sup><br> |                    | <b>2864</b> | .50 | 35       | .84             | White                       | B, C         | Low           |                     | 45.9%                         | \$\$       |

**PATTERNS**

| ILLUSION TWO/24            | ILLUSION FOUR/48                   | ILLUSION EIGHT/12          | ILLUSION THIRTY-TWO/6    |
|----------------------------|------------------------------------|----------------------------|--------------------------|
| The look of 2' x 2' panels | The look of 48" x 6" linear strips | The look of 12" x 12" tile | The look of 6" x 6" tile |
|                            |                                    |                            |                          |

**LEGEND**

**Low Emissions (VOC)**  
 Low-emitting performance meets CA Specification 01350 (CA Dept. of Health Services Standard Practice for the testing of VOC emissions) and is listed on the CHPS database for low-emitting materials. USG Certificate of Compliance for Low VOC Emissions also available on usg.com.

**ClimaPlus™ Warranty Performance<sup>7</sup>**  
 Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mould and mildew. Includes sag resistance performance.

**Firecode®**

**GRID PROFILE OPTIONS**

| A                     | B                 | C               |
|-----------------------|-------------------|-----------------|
| DX <sup>9</sup> /DXL™ | CENTRICITEE™ DXT™ | IDENTITEE™ DXI™ |
|                       |                   |                 |

**PHYSICAL DATA/NOTES**

|  |  |  |
|--|--|--|
| <p><b>Product literature</b><br/>                     Data sheet: SC2126E</p> <p><b>ASTM E1264 classification</b><br/>                     Type III, Form 2, Pattern CEK</p> <p><b>ASTM E84 and CAN/ULC S102 surface burning characteristics</b><br/>                     Class A<br/>                     Flame spread: 25<br/>                     Smoke developed: 50</p> | <p><b>Weight</b><br/>                     0.87-1.2 lbs./sq. ft.</p> <p><b>Thermal resistance</b><br/>                     R-1.7 (Class A)<br/>                     R-1.9 (Firecode)</p> <p><b>Maximum backloading</b><br/>                     See Warranty for details.</p> <p><b>Maintenance</b><br/>                     Can be cleaned easily with a soft brush or vacuum.</p> | <p><b>Notes</b></p> <ol style="list-style-type: none"> <li>For details, see LEED report tool at cgcdesignstudio.com.</li> <li>Fire-rated items: see UL design details.</li> <li>LR values are shown as averages.</li> <li>See colours selector for more information.</li> <li>Panels have a 15/16" routing.</li> <li>Panels have a 9/16" routing.</li> <li>For details, see Ceiling Systems Limited Warranty Commercial Applications (CSC2102) and ClimaPlus Ceilings Certification of Performance (SC2451).</li> <li>Not available in the following standard colours: Flat Black or Charcoal</li> </ol> |
|--|--|--|