

Rockfon® Facett™

1.00
NRC

Features & Benefits

- For industrial applications and parking garages
- Excellent sound absorption (NRC = 1.00)
- Excellent thermal insulation (up to R=14.0 and RSI=2.47)
- High fire performance
- Available in square lay-in

Applications

- Garage
- Light Industry
- Heavy Industry



Rockfon ceiling tiles are manufactured using advanced stone wool technology. All stone wool tiles benefit from:



**High Acoustic
Absorption**



**Class A Fire Rated
Performance**



**Moisture and Sag
Resistance**



**Smooth, Modern
Aesthetics**

Materials and Resources (MR)

- Waste Management Planning
- Interiors Life Cycle Impact Reduction
- Environmental Product Declarations
- Sourcing of Raw Materials
- Material Ingredients
- Waste Management

Indoor Environmental Quality (EQ)

- Low-Emitting Materials
- Interior Lighting
- Acoustic Performance

Recycled Content: up to 51%




Standard Panels

Edge Designation		Item Number	Modular Size (nominal)	NRC	AC	Fire Class	Light Reflectance	Sag Resistance (relative humidity)	Low VOC	lbs/sqft	sqft/carton
	SQ	5100	2' x 4' x 1 1/2"	1.00	-	A	0.68	up to 100%	✓	0.82	40
	SQ	5200	2' x 4' x 4"	1.00	-	A	0.68	up to 100%	✓	1.93	16

15/16" Suspension Systems

200, 1200 and Fire Rated systems

SQ - Square Lay-In





Rockfon Facett Properties

Material

Stone wool (Mineral Wool) ceiling tiles with factory applied latex paint on glass scrim surface
ASTM E1264 CLASSIFICATION: Type XX - Stone wool base with membrane-faced overlay, Pattern E



Fire Performance

Surface burning characteristics:
UL723 (ASTM E84) Flame Spread Index: 0
Smoke Developed Index (UL Labeled): 5
CAN/ULC S102 Flame Spread Index: 5
Smoke Developed Index: 0



Environment

Up to 51% recycled content.
Recycled content based on U.S. manufacturing.



Thermal Insulation

R Value (BTU Units): 5.3 - 14
RSI Value (Watts Units): 0.92 - 2.47



Sustainability

Many of Rockfon stone wool acoustic solutions are GREENGUARD Gold low VOC certified and meet the State of California's Department of Public Health Services Standard Practice for Specification Section 01350 (California Section 01350) for testing chemical emissions.

Selected potential applications: LEED, WELL, CHPS, Green Globes, BREEAM Int. and CALGreen.



Warranty

30-Year Limited Product Warranty.
See rockfon.com



Hygiene

Stone wool provides no sustenance to microorganisms



Cleaning

- Vacuum
- Damp cloth



Greenguard Gold Certified
for Office and Educational
Environments

112619

Rockfon

4849 S. Austin Ave.
Chicago, IL 60638 USA

2019 | Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.
© ROCKWOOL International A/S 2018. All rights reserved.

® denotes a trademark that is registered in the United States of America.

Tel. +1-800-323-7164

Fax. +1-800-222-3744

rockfon.com