

Rockfon® Impact™

0.85 NRC

Features & Benefits

- A reinforced glass scrim enhancing impact resistance
- Good sound absorption (NRC = 0.85)
- High fire performance
- High light reflectance (LR = 0.86)
- Available in square lay-in

Applications

- Recreational Center
- Convention Center



Rockfon ceiling tiles are manufactured using advanced stone wool technology. All stone wool tiles benefit from:



High Acoustic Absorption



Class A Fire Rated Performance



Moisture and Sag Resistance



Smooth, Modern Aesthetics

Rockfon® Impact™

Standard Panels

LEED® v4 Highlights

Materials and Resources (MR)
Waste Management Planning
Interiors Life Cycle Impact Reduction
Environmental Product Declarations

Indoor Environmental Quality (EQ)

- Low-Emitting Materials
 ✓ Interior Lighting
 ✓ Acoustic Performance
















Packaging Information

Edge Designation		Item Number	Modular Size (nominal)	NRC	AC	Fire Class	Light Reflectance	Sag Resistance (relative humidity)	Low VOC	lbs/ sqft	sqft/ carton
Square Lay-In	SQ	4100	2' x 2' x 3/4"	0.85	-	А	0.86	up to 100%	✓	0.45	80
	SQ	4200	2' x 2' x 1 1/2"	0.85	-	А	0.86	up to 100%	✓	0.82	40





Rockfon Impact Properties

Material

Stone wool (Mineral Wool) ceiling tiles with factory applied latex paint on reinforced glass scrim to increase impact resistance ASTM E1264 CLASSIFICATION: Type XX - Stone wool base with membrane-faced overlay, Pattern E



Fire Performance

Surface burning characteristics: UL723 (ASTM E84) Flame Spread Index: 0 Smoke Developed Index (UL Labeled): 5 CAN/ULC S102 Flame Spread Index: 5 Smoke Developed Index: 0



Environment

Up to 27% recycled content. Recycled content based on European manufacturing.



Thermal Insulation

R Value (BTU Units): 2.6 - 5.3 RSI Value (Watts Units): 0.46 - 0.92



Sustainability

Many of Rockfon stone wool acoustic solutions are GREENGUARD Gold low VOC certified and meet the State of California's Department of Public Health Services Standard Practice for Specification Section 01350 (California Section 01350) for testing chemical emissions.

Selected potential applications: LEED, WELL, CHPS, Green Globes, BREEAM Int. and CALGreen.



Warranty

30-Year Limited Product Warranty. See rockfon.com



Hygiene

Stone wool provides no sustenance to microorganisms



Cleaning

- Vacuum
- Damp cloth



Impact Resistance

Rockfon Impact's capability to withstand incidental or occasional ball impact has been tested. For more details, please contact customer service.



Greenguard Gold Certified for Office and Educational Environments

Rockfon

112619

4849 S. Austin Ave. Chicago, IL 60638 USA

Tel. +1-800-323-7164 Fax. +1-800-222-3744 rockfon.com

2019 | Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.

[©] ROCKWOOL International A/S 2018. All rights reserved.

[®] denotes a trademark that is registered in the United States of America.