

Part of the ROCKWOOL Group

Rockfon[®] Industrial[™] Opal

1.05 NRC

Features & Benefits

- For industrial applications
- Excellent sound absorption (NRC = 1.05)
- High fire performance
- To create a new ceiling or place under an existing one
- Available in square lay-in

Applications

- Light Industry
- Heavy Industry



Rockfon ceiling tiles are manufactured using advanced stone wool technology. All stone wool tiles benefit from:



High Acoustic Absorption





Moisture and Sag Resistance



Smooth, Modern Aesthetics

Rockfon® Industrial[™] Opal

LEED® v4 Highlights

Materials and Resources (MR)

Waste Management Planning Interiors Life Cycle Impact Reduction Environmental Product Declarations

Indoor Environmental Quality (EQ)

- Low-Emitting Materials Interior Lighting Acoustic Performance

c										
Standard Panels			S S S S S S S S S S S S S S S S S S S	and		¢.	\bigcirc		Packaging Information	
Edge Designation	ltem Number	Modular Size (nominal)	NRC	AC	Fire Class	Light Reflectance	Sag Resistance (relative humidity)	Low VOC	lbs/ sqft	sqft/ carton
Square Lay-In	6100	2' x 4' x 2"	1.05	-	А	0.64	up to 100%	~	0.8	32

15/16" Suspension Systems
200, 1200 and Fire Rated systems
SQ - Square Lay-In



Rockfon Industrial Opal Properties

Material

Stone wool (Mineral Wool) ceiling tiles with factory applied latex paint on glass scrim surface ASTM E1264 CLASSIFICATION: Type XX - Stone wool base with membrane-faced overlay, Pattern G



Fire Performance

Surface burning characteristics: UL723 (ASTM E84) Flame Spread Index: 0 Smoke Developed Index (UL Labeled): 5 CAN/ULC S102 Flame Spread Index: 5 Smoke Developed Index: 0



Sustainability

Many of Rockfon stone wool acoustic solutions are GREENGUARD Gold low VOC certified and meet the State of California's Department of Public Health Services Standard Practice for Specification Section 01350 (California Section 01350) for testing chemical emissions.

Selected potential applications: LEED, WELL, CHPS, Green Globes, BREEAM Int. and CALGreen.



Cleaning

Vacuum



Greenguard Gold Certified for Office and Educational Environments

2019 I Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors. © ROCKWOOL International A/S 2018. All rights reserved.

[®] denotes a trademark that is registered in the United States of America.



Environment

Up to 51% recycled content. Recycled content based on U.S. manufacturing.



Warranty

30-Year Limited Product Warranty. See rockfon.com



Thermal Insulation

R Value (BTU Units): 7.0 RSI Value (Watts Units): 1.23



Hygiene

Stone wool provides no sustenance to microorganisms

112619

Rockfon

4849 S. Austin Ave. Chicago, IL 60638 USA

Tel. +1-800-323-7164 Fax. +1-800-222-3744 rockfon.com