

Skim coat and prime new drywall with a whiter, smoother finish



SHEETROCK®

TUFF-HIDE™ Primer-Surfacer

- Enhanced formulation dries whiter and smoother
- Achieves a Level 5 wallboard finish in one step
- Provides superior abrasion resistance



SHEETROCK® TUFF-HIDE™ Primer-Surfacer provides an affordable Level 5 wallboard finish – now with an enhanced formulation that provides whiter and smoother results. With the proper spray equipment and technique, TUFF-HIDE Primer-Surfacer applies quickly and evenly and generally requires no sanding for an ultra high-end look. A vinyl acrylic latex-based coating, TUFF-HIDE Primer-Surfacer also provides increased resistance to surface abrasion.

Uses

- Designed especially for interiors over new drywall
- Provides the same high-quality drywall finish as two-step skim coating and priming
- Meets industry approved standards for Level 5 gypsum board finish

Applications

- Applies with professional airless spray equipment
- Tints with up to 15 ml (2 ounces) per gallon of universal colorant
- Can be painted after overnight drying
- Can be left unpainted in ceiling applications where a flat white finish is desired
- See the TUFF-HIDE Primer-Surfacer Data Sheet (EJC-0J56) for more information

Properties

- Covers approximately 46 - 58 m² (500 - 625 sq ft) per 18.9 L pail for most applications
- Dries to touch in approximately 60-90 minutes for most applications under normal drying conditions
- Provides increased resistance to surface abrasion
- Sands easily, although sanding is generally unnecessary with proper spraying technique

Note

Products described here may not be available in all geographic markets. Consult your CGC sales office or representative for information.

Trademarks

The CGC logo is a trademark of CGC Inc. CGC Inc. is a licensed user of the trademarks SHEETROCK and TUFF-HIDE.

Notice

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss cause by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

Safety First!

Follow good safety and industrial hygiene practices during handling and installation of all products and systems. Take necessary precautions and wear the appropriate personal protective equipment as needed. Read material safety data sheets and related literature on products before specification and/or installation.