


STOCK NUMBER	SIZE	LENGTH	PCS PER BOX
9210	3/8"	10'	25



SUBMITTAL SHEET

Product(s): Trim-Tex Super Seal Tear Away™ Bead

Description: Trim-Tex Super Seal Tear Away Beads are designed to finish rough drywall ends and seal gaps.

Advantages: Comes with a full 5/16" tear-off leg that acts as a guide for the taping knife as well as a protective masking for taping and mudding. The semi round gasket compress upon installation to form a permanent seal that effectively reduces sound transmission, replaces caulk and provides structural relief at the panel perimeter. Made from rust proof, dent resistant PVC to reduce jobsite and handling damage. Does not contain cellulose, a potential food source for mold

Limitations: Product is designed for interior use.

Applicable Standards: Rigid PVC products made by Trim-Tex meet ASTM specifications D3678-97 Class 2, D1784-03, C1047-99 and achieve a Class A rating for flame spread and smoke developed when tested under ASTM E84-10.

Surface Characteristics: Trim-Tex products are made from PVC. PVC does not support combustion and is self extinguishing when the source of flame or heat is removed.

Installation:

Method 1: To install the bead, cut the bead to length. For optimum performance, leave a 1/4" gap between the edge of the drywall and the opposite substrate. Use a 1/4" piece of plywood or drywall as a gauge to ensure a consistent gap. Spray the bead with Trim-Tex 847 Spray Adhesive. Immediately apply to the drywall. Once in position, press the legs into place using a Trim-Tex installation tool or the handle of your taping knife.

Method 2: Cut the bead to length. Leave a 1/4" gap between the edge of the drywall and the opposite substrate. Once in position, staple the mud leg into place every 6"-8" with 1/2" long divergent staples.

Preferred: Combination of 847 Spray adhesive and staples as detailed above.

Finishing: Once mudding is complete, remove tear-off leg for a clean, sharp look. The flexible gasket contains a UV stabilizer and does not need to be painted. To paint the rest always use a high quality paint.

Accessories: 847 Spray Adhesive, Staple Guns and Divergent Staples, Trim-Tex Sanding Blocks & Abrasive Products, Mud-Max Drywall Compound Additive, North by Honeywell - Safety Products distributed by Trim-Tex.

Job Name_____

Contractor

Date



