

TUNDRA®

Square Lay-in & Tegular
medium texture



Tundra® panels with Suprafine® 9/16" suspension system (Pgs. 400-401)

Durable Tundra® panels have a medium-textured visual, and are impact- and scratch-resistant.

KEY SELECTION ATTRIBUTES

- Durable
 - Impact-resistant
 - Scratch-resistant
- 30-Year Limited System Warranty against visible sag, mold, and mildew

TYPICAL APPLICATIONS


- Offices
- Schools
- Corridors

COLOR



White
(WH)

DETAILS (Other Suspension Systems compatible. Refer to listing on page 310.)



1. Tundra® Beveled Tegular
2. Tundra with Suprafine® 9/16" suspension system

TUNDRA®

Square Lay-in & Tegular medium texture

UP TO **35%** RECYCLED CONTENT

Calculate LEED contribution at armstrongceilings.com/greengenie

LEED®

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/extended producer resp.
- bio-based materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics




LOCATION DEPENDENT

VISUAL SELECTION

PERFORMANCE SELECTION


Dots represent high level of performance.

\$\$\$

Edge Profile	Susp. Dwg. Pgs. 407-411 armstrongceilings.com/catdwgs	Item No.	Dimensions (Inches)	UL Classified Acoustics	NRC + CAC	Total Acoustics ¹	Fire Performance	Light Reflect	Anti-Mold & Mildew	Sag Resist	Certified Low VOC Emissions	Impact	Scratch	Recycled Content	Recycle Program	30-Yr Warranty
TUNDRA®																
	15/16" Square Lay-in	1	301	24 x 24 x 5/8"	0.50	33	Class A	0.87	•	•	•	•	•	Std	•	•
		1	302	24 x 48 x 5/8"	0.50	35	Class A	0.87	•	•	•	•	•	Std	•	•
		1	Other Size Panels	W: 24" / L: 24" – 48" 5/8" Thick	N/A	N/A	Class A	0.87	•	•	•	•	•	Std	•	•
	15/16" Beveled Tegular	15	303	24 x 24 x 5/8"	0.50	33	Class A	0.87	•	•	•	•	•	Std	•	•
		15	305	24 x 48 x 5/8"	0.50	35	Class A	0.87	•	•	•	•	•	Std	•	•
		15	Other Size Panels	W: 24" / L: 24" – 48" 5/8" Thick	N/A	N/A	Class A	0.87	•	•	•	•	•	Std	•	•
	9/16" Beveled Tegular	29, 44, 48, 52, 56	304	24 x 24 x 5/8"	0.50	33	Class A	0.87	•	•	•	•	•	Std	•	•
		29, 44, 48, 52, 56	Other Size Panels	W: 24" / L: 24" – 48" 5/8" Thick	N/A	N/A	Class A	0.87	•	•	•	•	•	Std	•	•

¹Total Acoustics® ceiling panels have an ideal combination of noise reduction and sound-blocking performance in one product.

SUSPENSION SYSTEMS



PHYSICAL DATA

Material
Wet-formed, high-density mineral fiber

Surface Finish
Factory-applied latex paint with scuff-resistant spatter coat

Fire Performance
ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less (UL labeled).

ASTM E1264 Classification
Type III, Form 2, Pattern C E
Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Acoustical Testing
CAC testing conducted using Prelude® XL® suspension system for 15/16" edge detail and Silhouette® suspension system for 9/16" edge detail.

Mold/Mildew Protection
Ceiling panels with BioBlock® performance resist the growth of mold and mildew.

Insulation Value
R Factor – 1.7 (BTU units)
R Factor – 0.30 (Watts units)

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com

Weight; Square Feet/Carton
301, 302, 305 – 1.09 lbs/SF; 64 SF/ctn
303, 304 – 1.10 lbs/SF; 48 SF/ctn

Minimum Order Quantity
1 carton, excludes other size panels.

Metric Items Available
302M, 303M, 305M, 304M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.