WB-UAD Utility Access Door



- REPRESENTED BY -----


DETAIL & SUBMITTAL SHEET


Project: Date:

Specification Reference:

Contractor:

Architect:





ELEVATION

SECTION DETAIL

CONSTRUCTION FEATURES:

Door and Trim: 16 ga. steel. Trim being 1-1/2" wide. **Return Frame:** 16 ga. steel having a depth of 1-1/4".

Hinge: One piece hidden pivot rod hinge.

Latches: Flush, stainless steel cam operated with screwdriver. Latches are positioned expected bings as well as top and bottom as larger sizes.

tioned opposite hinge as well as top and bottom on larger sizes.

Finish: Electrostatically applied baked grey enamel coat over rust-inhibiting phosphate treated steel. This coating can be used as a finish or as a prime coating

Packaging: By the case; 5 doors per case, except 24" x 24" size — 3 per case, or individually boxed.

Optional Available: (AT EXTRA COST)Keyed Cylinder Lock with 2 keys

Stainless Steel #304

A B Door Size	Wall Opening	Hinges	Cam Latch		ng Wt. bs. Case
6"x6"	61/8"x61/8"	1	1	11/2	81/2
8"x8"	81/8"x81/8"	1	1	2 1/2	131/2
10"x10"	101/8"x101/8"	1	1	4	21
12"x12"	121/8"x121/8"	1	1	5	26
14"x14"	141/8"x141/8"	1	3	6	32
16"x16"	161/8"x161/8"	1	3	71/2	391/2
18"x18"	181/8"x181/8"	1	3	9	48
24"x24"	241/8"x241/8"	1	4	15	45



Corporate Office: 777 Tapscott Rd. Scarborough, Ontario

Phone: (416) 299-7767 Fax: (416) 299-8039 Toll free tel.: 1-888-575-1132 Toll free fax: 1-888-575-1134